



Exterior Wood Cleaner

Removes dirt and stains

Exterior Wood Cleaner was developed for the thorough cleaning of all types of wood surfaces, such as terraces, garden furniture, fences, canopies, doors and windows. The product quickly and efficiently dissolves dirt, thereby assuring an optimal surface for subsequent treatment.

- Effective removal of dirt, stain and grease
- Prepares the surface for subsequent treatment
- Economical and easy to use
- Ideal for all species of wood

Application area

Suitable for both new and aged wood, this product is perfect for a variety of surfaces including garden furniture, terraces, fences, canopies, window frames, doors, and carports. Additionally, it can be applied to masonry and concrete surfaces..

Work description

Preparation

Treatment should only be performed in dry weather conditions. Avoid direct sunlight and excessive heat.

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

Mix Exterior Wood Cleaner with water in a ratio of 100 ml to 1.0 L of water. If the wood is very dirty, a stronger dosage may be used. Apply the cleaner evenly with a brush or spray. Leave the cleaner to work for 5 minutes. Scrub along the grain of the wood with a stiff brush or broom until the surface is clean. Rinse the surface thoroughly with plenty of water and allow the wood to dry for at least 24 hours.

Please note

Exterior Wood Cleaner can also be used on masonry and concrete.

Drying time

Drying time: 24-48 hours at 20°C

Surface Dry: 24-48 hours at 20°C

Technical data

Declaration: >5% ≤15%: Non-ionic surfactants.

Density: 1.00-1.10 g/ml.

pH-value: pH 10-11

Shelf life: 3 years

Application Temperature: +10-25°C, ideally cloudy weather.

Coverage: 10-50 m²/L

Colours: Colourless

Cleaning of tools: Use water

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight).
Store frost-free during winter and cool during summer.

Packaging: 1 L, 2.5 L

Dilution: Water

Odour: Faint

Mixing ratio: 100 ml for 1.0 L water

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.