



Intensive Wood Cleaner, Spray

Treatment preparation

Intensive Wood Cleaner is a ready-to-use spray designed for deep cleaning all types of interior woodwork, including furniture, staircases, doors, panels, and worktops. It is effective on oiled, waxed, painted, or lacquered surfaces. Specifically formulated, WOCA Intensive Wood Cleaner is ideal for preparing wooden floors for subsequent treatments.

- Ready to use
- For untreated, lacquered, oiled or soaped indoor surfaces
- Basic cleaning and grease removal

Application area

For cleaning of new, old, untreated, sanded and treated wood. Ideal as a priming cleaner for all species of wood.

Work description

Preparation

Use WOCA Wood Stain Remover for particularly stubborn stains.

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

Shake the bottle thoroughly before use. Spray Intensive Wood Cleaner onto the surface. Allow the mixture to work for 5 minutes, before wiping down with clean water. Leave the surface to dry for 2-8 hours, depending on subsequent treatments.

Please note

Intensive Wood Cleaner leaves oiled and wax-treated surfaces completely free of oils, so re-oiling/waxing after cleaning is required. Lacquered surfaces should be refreshed with WOCA Master Care.

Drying time

Drying time: 2-8 hours at 20°C

Recommendation: This Product is NOT to be used for regular, everyday cleaning.

Technical data

Declaration: less than 5%: BENZISOTHIAZOLINONE.

Density: 1.00-1.10 g/ml.

pH-value: pH 10-11

Shelf life: 3 years

Application Temperature: +15-30°C and approx. 50% air humidity.

Coverage: 6-10 m²/L

Colours: Colourless

Cleaning of tools: Use water

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging: 750 ML

Odour: Faint

Mixing ratio: Ready to use. Do not dilute.

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.