



Tannin Spot Remover

Neutralises discolouration

Tannin Spot Remover effectively removes black spots caused by tannin/water reaction on interior wood surfaces without any harsh or bleaching chemicals.

- Removes black watermarks from wood
- Ready mixed - Easy to use
- Neutralises tannin
- Water Based
- for indoor and outdoor use

Application area

May be used on unfinished, soaped, oiled or waxed interior wood surfaces such as floors, furnitures and tables.

Work description

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

Spray Tannin Spot Remover evenly on the stain directly from the bottle. Leave the Tannin Spot Remover to dissolve the stain for 30-60 min. Wipe with cloth wrung in lukewarm water. Repeat operation if necessary. When the floor is completely dry, apply the original surface finish, e.g. oil, wax or soap to re-establish the protection of the surface.

Drying time

Drying time: 30-60 minutes at 20°C

Technical data

Declaration: less than 5%: BENZISOTHIAZOLINONE, 2-BROMO-2-NITROPROPANE-1,3-DIOL.

Density: 0.95-1.00 g/ml.

pH-value: pH 2-3

Shelf life: 2 years

Application Temperature: +15-30°C and approx. 50% air humidity.

Colours: Colourless

Cleaning of tools: Use water

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging: 250 ML

Odour: Odourless

Mixing ratio: Ready to use. Do not dilute.

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.