

Ø60mm konisk mast for park- & vejarmaturer. Nedgravning. Topmontage.

Art nr.	Type
802-70-030-2	Ø60/110mm konisk mast. LPH 3,00M f/nedgravning. 3,60/3,00M. Varmgalvaniseret stål.
802-70-035-2	Ø60/117mm konisk mast. LPH 3,50M f/nedgravning. 4,10/3,50M. Varmgalvaniseret stål.
802-70-040-2	Ø60/127mm konisk mast. LPH 4,00M f/nedgravning. 4,80/4,00M. Varmgalvaniseret stål.
802-70-045-2	Ø60/134mm konisk mast. LPH 4,50M f/nedgravning. 5,30/4,50M. Varmgalvaniseret stål.
802-70-050-2	Ø60/130mm konisk mast. LPH 5,00M f/nedgravning. 5,80/5,00M. Varmgalvaniseret stål.
802-70-060-2	Ø60/130mm konisk mast. LPH 6,00M f/nedgravning. 7,00/6,00M. Varmgalvaniseret stål.

Tilbehør:

800-145-500	Isoleringsindsats (skumklods) Ø135/60 for master Ø133/Ø108mm.
920-634-200	Vingefundament for Ø108/Ø133mm mast. Galvaniseret plade.
924-100-012	Sikringsindsats for Ø108/Ø133mm master. 1 neozed sikring.
924-100-002	Sikringsindsats MINI for Ø108/Ø133mm master. 1 neozed sikring. (Passer t/LPH 2,50M og 3,00M)
000-299-900	Transientbeskyttelse >10 kV.

Ovenstående master kan pulverlakeres på forespørgsel.

Priserne kan variere, da der tages forbehold for stål- og oliepriser.

	A	B	C	D	E
Konisk mast LPH 3,0M	3600	3000	60	500	110
Konisk mast LPH 3,5M	4100	3500	60	600	117
Konisk mast LPH 4,0M	4800	4000	60	600	127
Konisk mast LPH 4,5M	5300	4500	60	600	130
Konisk mast LPH 5,0M	5800	5000	60	600	134
Konisk mast LPH 6,0M	7000	6000	60	600	134

