

Ø60mm bertlet mast for park- & vejarmaturer. Nedgravning. Topmontage.

Art nr.	Type
802-10-025-2	Ø60/108mm bertlet mast. LPH 2,50M f/nedgravning. 3,00/2,50M. Varmgalvaniseret stål.
802-10-030-2	Ø60/108mm bertlet mast. LPH 3,00M f/nedgravning. 3,60/3,00M. Varmgalvaniseret stål.
802-10-035-2	Ø60/108mm bertlet mast. LPH 3,50M f/nedgravning. 4,10/3,50M. Varmgalvaniseret stål.
802-10-040-2	Ø60/108mm bertlet mast. LPH 4,00M f/nedgravning. 4,80/4,00M. Varmgalvaniseret stål.
802-10-045-2	Ø60/108mm bertlet mast. LPH 4,50M f/nedgravning. 5,30/4,50M. Varmgalvaniseret stål.
802-10-050-2	Ø60/108mm bertlet mast. LPH 5,00M f/nedgravning. 5,80/5,00M. Varmgalvaniseret stål.
802-10-055-2	Ø60/108mm bertlet mast. LPH 5,50M f/nedgravning. 6,30/5,50M. Varmgalvaniseret stål.
802-10-060-2	Ø60/114mm bertlet mast. LPH 6,00M f/nedgravning. 7,00/6,00M. Varmgalvaniseret stål.

Tilbehør:

800-145-500	Isoleringsindsats (skumklods) Ø135/60 for master Ø133/Ø108mm.
920-634-200	Vingefundament for Ø108/Ø133mm mast. Galvaniseret plade.
924-100-012	Sikringsindsats for Ø108/Ø133mm master. 1 neozed sikring.
800-13-108-2	Beslag f/OPUS74 stikkontakt (excl). Passer t/Ø108mm mast. Varmgalvaniseret stål.
000-299-900	Transientbeskyttelse >10 kV.

Ovenstående master kan pulverlakeres på forespørgsel.

Priserne kan variere, da der tages forbehold for stål - og oliepriser.

	A	B	C	D	E	F	G
Bertlet mast LPH 2,5M	3000	2500	60	1500	500	1500	108
Bertlet mast LPH 3,0M	3600	3000	60	1600	500	2000	108
Bertlet mast LPH 3,5M	4100	3500	60	1600	500	2500	108
Bertlet mast LPH 4,0M	4800	4000	60	2100	600	2700	108
Bertlet mast LPH 4,5M	5300	4500	60	2100	600	3200	108
Bertlet mast LPH 5,0M	5800	5000	60	2600	600	3200	108
Bertlet mast LPH 5,5M	6300	5500	60	3200	600	3100	108
Bertlet mast LPH 6,0M *	7000	6000	60	2300	500	4700	114

* Bundrør Ø114: 2300mm. Mellemrør Ø89: 2000mm. Toprør Ø60: 2700mm.

