

Art.No.	Type
<b>674-21B-204-K2</b>	brIQ G2 street fitting excl pole. FastFlex LED 11W/740/2140Lm.. Clear PC. CL.II. Hot galvanized steel.
<b>674-22B-204-K2</b>	brIQ G2 street fitting excl pole. FastFlex LED 20W/740/3761Lm. Clear PC. CL.II. Hot galvanized steel.
<b>674-23B-204-K2</b>	brIQ G2 street fitting excl pole. FastFlex LED 27W/740/4773Lm. Clear PC. CL.II. Hot galvanized steel.
<b>+ PROG01</b>	Dimmer profil 01 = ON/OFF without dimming
<b>+ PROG07</b>	Dimmer profil 07 = -40% 20:00-22:00, -60% 22:00-05:00, -40% 05:00-06:00. (stepdimmer)
	Other dimming profiles on request.
<b>+ Topmounting</b>	Fitting top-mounted.
<b>+ Sidemounting</b>	Fitting side-mounted.

**Accessories:**

<b>802-10-030-2</b>	Ø60/108mm stepped pole LPH 3,00M f/burial. 3,60/3,00M. Hot galvanized steel.
<b>800-145-500</b>	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
<b>920-634-200</b>	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
<b>924-100-012</b>	Fuse inset for Ø108/Ø133mm poles. 1 neozed fuse.
<b>800-13-108-2</b>	Bracket f/OPUS74 outlet (excl). Fits t/Ø108mm pole. Hot galvanized steel.
	----- Several variations of poles, accessories and spare parts. See page 103-125 -----

**Variation options:**

- Also available with 3000K.
- Possibility of project-oriented configuration.
- Available with other lenses.

**Key features:**

- 10 year anti-corrosion warranty. (Hot galvanized)
- 10 year reorder warranty.
- 5 year LED & driver warranty.
- Life expectancy: 100.000 hours.
- Integrated >10 kV surge protection.
- Supplied with 5M cable.

