

Art.No.	Type
155-415-245-K2	HANS spot base. Fortimo SLM 15W/840/2811Lm. CL.II. Clear PC-Lens. Hot galvanized steel.
155-415-x45-K2*	HANS spot base. Fortimo SLM 15W/840/2811Lm. CL.II. Clear PC-Lens. Powder coated.*
155-420-245-K2	HANS spot base. Fortimo SLM 20W/840/3626Lm. CL.II. Clear PC-Lens. Hot galvanized steel.
155-420-x45-K2*	HANS spot base. Fortimo SLM 20W/840/3626Lm. CL.II. Clear PC-Lens. Powder coated.*
155-432-245-K2	HANS spot base. Fortimo SLM 32W/840/5386Lm. CL.II. Clear PC-Lens. Hot galvanized steel.
155-432-x45-K2*	HANS spot base. Fortimo SLM 32W/840/5386Lm. CL.II. Clear PC-Lens. Powder coated.*

Accessories:

831-10-N-12-2	Square pole 1,20x0,70M f/burial. Coat hanger and turn securing welded. Hot galvanized steel.
831-10-N-12-x*	Square pole 1,20x0,70M f/burial. Coat hanger and turn securing welded. Powder coated.*
920-831-200	Pole bracket side mounting f/HANS spot. Hot galvanized steel.
920-831-x00*	Pole bracket side mounting f/HANS spot. Powder coated.*
920-833-200	Bollard bracket Ø133mm f/HANS spot. Topmounting. Hot galvanized steel.
920-833-x00*	Bollard bracket Ø133mm f/HANS spot. Topmounting. Powder coated.*
880-120-200	Ø133mm pole f/burial. 1,20/0,70M. CL.I. Hot galvanized steel.
880-120-x00*	Ø133mm pole f/burial. 1,20/0,70M. CL.I. Powder coated.*
920-634-200	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.

* Powder coated: Standard colors are Anthracite RAL7016, Black RAL9005. Other RAL colors on request with extra price. Find the final Art.No. by replacing "x" with the color code. Anthracite: x=5, Black: x=9, Special: x=P.

Note: The spot base is ex. accessories.

Variation options:

- Also available with 3000K.

Key features:

- 10 year anti-corrosion warranty. (Hot galvanized)
- 10 year reorder warranty.
- 5 year LED & driver warranty.
- Life expectancy: 50.000 hours.
- Integrated >10 kV surge protection.

