

Art.No.	Type
553-13B-235	OskarLED bollard fitting excl pole. LEDstrip 13W/830/2134Lm. Clear PC-screen. CL.I. Hot galvanized steel.
553-13B-245	OskarLED bollard fitting excl pole. LEDstrip 13W/840/2246Lm. Clear PC-screen. CL.I. Hot galvanized steel.
553-13B-x35*	OskarLED bollard fitting excl pole. LEDstrip 13W/830/2134Lm. Clear PC-screen. CL.I. Powder coated.*
553-13B-x45*	OskarLED bollard fitting excl pole. LEDstrip 13W/840/2246Lm. Clear PC-screen. CL.I. Powder coated.*
	Additional charge for protection class II double insulated.

Accessories:

880-120-200	Ø133mm pole f/burial. 1,20/0,70M. CL.I. Hot galvanized steel.
880-120-x00*	Ø133mm pole f/burial. 1,20/0,70M. CL.I. Powder coated.*
	Additional charge for pole for class II bollard fittings. Delivered with mounting hatch. See page 106.
800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
920-634-200	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
800-13-133-2	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Hot galvanized steel.
800-13-133-x*	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Powder coated.*
	----- Several variations of poles, accessories and spare parts. See page 103-125 -----

* Powder coated: Standard colors are Anthracite RAL7016, Black RAL9005. Other RAL colors on request with extra price. Find the final Art.No. by replacing "x" with the color code. Anthracite: x=5, Black: x=9, Special: x=P.

Note: OskarLED in Anthracite RAL7016 is called ZENTA and is sold exclusively through www.solar.dk

Key features:

- 10 year anti-corrosion warranty. (Hot galvanized)
- 10 year reorder warranty.
- 5 year LED & driver warranty.
- Life expectancy: 50.000 hours.
- Integrated >10 kV surge protection.

