

Art.No.	Type
640-112-245	TEGO bollard fitting excl pole. DLM ES 10W/840/1100Lm. Acrylic lens clear. Glass satine. CL.I. Hot galvanized steel.
640-112-x45*	TEGO bollard fitting excl pole. DLM ES 10W/840/1100Lm. Acrylic lens clear. Glass satine. CL.I. Powder coated.*
	Additional charge for protection class II double insulated.
Accessories:	
880-120-200	Ø133mm pole f/burial. 1,20/0,70M. CL.I. Hot galvanized steel.
880-120-x00*	Ø133mm pole f/burial. 1,20/0,70M. CL.I. Powder coated.*
	Additional charge for pole for class II bollard fittings. Delivered with mounting hatch. See page 106.
800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
920-634-200	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
800-13-133-2	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Hot galvanized steel.
800-13-133-x*	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Powder coated.*
000-299-900	Surge protector >10 kV.
	----- Several variations of poles, accessories and spare parts. See page 103-125 -----

* Powder coated

Standard colors are Anthracite RAL7016, Black RAL9005. Other RAL colors on request with extra price.
Find the final Art.No. by replacing "x" with the color code. Anthracite: x=5, Black: x=9, Special: x=P.

Variation options:

• Also available with 3000K.

Key features:

• 10 year anti-corrosion warranty. (Hot galvanized)
• 10 year reorder warranty.
• 5 year LED warranty.
• 230V LED module. No driver.
• Life expectancy: 50.000 hours.

