Ø60mm stepped pole for park- & street fittings. Burial. Top mounted.

Art.No.	Type
802-10-025-2	Ø60/108mm stepped pole. LPH 2,50M f/burial. 3,00/2,50M. Hot galvanized steel.
802-10-030-2	Ø60/108mm stepped pole. LPH 3,00M f/burial. 3,60/3,00M. Hot galvanized steel.
802-10-035-2	Ø60/108mm stepped pole. LPH 3,50M f/burial. 4,10/3,50M. Hot galvanized steel.
802-10-040-2	Ø60/108mm stepped pole. LPH 4,00M f/burial. 4,80/4,00M. Hot galvanized steel.
802-10-045-2	Ø60/108mm stepped pole. LPH 4,50M f/burial. 5,30/4,50M. Hot galvanized steel.
802-10-050-2	Ø60/108mm stepped pole. LPH 5,00M f/burial. 5,80/5,00M. Hot galvanized steel.
802-10-055-2	Ø60/108mm stepped pole. LPH 5,50M f/burial. 6,30/5,50M. Hot galvanized steel.
802-10-060-2	Ø60/114mm stepped pole. LPH 6,00M f/burial. 7,00/6,00M. Hot galvanized steel.
Accessories:	
800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
920-634-200	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
924-100-012	Fuse inset for Ø108/Ø133mm poles. 1 neozed fuse.
800-13-108-2	Fitting for OPUS74 exterior socket (excl). f/Ø108mm poles. Hot galvanized steel.
000-299-900	Surge protecter >10 kV.

Can be powder coated on request.

The prices are on request and depends for steel, oil and raw material.

	A	B	C	D	E	F	G
Stepped pole LPH 2,5M	3000	2500	60	1500	500	1500	108
Stepped pole LPH 3,0M	3600	3000	60	1600	500	2000	108
Stepped pole LPH 3,5M	4100	3500	60	1600	500	2500	108
Stepped pole LPH 4,0M	4800	4000	60	2100	600	2700	108
Stepped pole LPH 4,5M	5300	4500	60	2100	600	3200	108
Stepped pole LPH 5,0M	5800	5000	60	2600	600	3200	108
Stepped pole LPH 5,5M	6300	5500	60	3200	600	3100	108
Stepped pole LPH 6,0M*	7000	6000	60	2300	500	4700	114

* Bottom tube Ø114: 2300mm. Middle tube Ø89: 2000mm. Top tube Ø60: 2700mm.

