

Ø133mm poles for bollard fittings. Burial. CL.I.

Art.No.	Type
880-120-200	Ø133mm pole. 1,20/0,70M f/burial. CL.I. Hot galvanized steel.
880-120-000	Ø133mm pole. 1,20/0,70M f/burial. CL.I. Rusty.
880-120-300	Ø133mm pole. 1,20/0,70M f/burial. CL.I. Solid copper.
880-120-x00*	Ø133mm pole. 1,20/0,70M f/burial. CL.I. Powder coated.*
880-150-200	Ø133mm pole. 1,50/1,00M f/burial. CL.I. Hot galvanized steel.
880-150-300	Ø133mm pole. 1,50/1,00M f/burial. CL.I. Solid copper.
880-150-x00*	Ø133mm pole. 1,50/1,00M f/burial. CL.I. Powder coated.*
880-200-200	Ø133mm pole. 2,00/1,40M f/burial. CL.I. Hot galvanized steel.
880-200-300	Ø133mm pole. 2,00/1,40M f/burial. CL.I. Solid copper.
880-200-x00*	Ø133mm pole. 2,00/1,40M f/burial. CL.I. Powder coated.*

Accessories:

800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
920-634-200	Turn securing for Ø108/Ø133mm pole. Hot galvanized plate.
800-13-133-2	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Hot galvanized steel.
800-13-133-x*	Bracket f/OPUS74 outlet (excl). Fits t/Ø133mm pole. Powder coated.*

* Powder coated: Standard colors are Anthracite RAL7016, Black RAL9005. Other RAL colors on request with extra price. Find the final Art.No. by replacing "x" with the color code. Anthracite: x=5, Black: x=9, Special: x=P.

	A	B	C
Pole 1,20/0,70M	1200	700	133
Pole 1,50/1,00M	1500	1000	133
Pole 2,00/1,40M	2000	1400	133

