

Art.Nr.	Type
710-31A-235	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 12W/830/2121Lm. CL.I. Hot galvanized steel.
710-31A-245	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 12W/840/2121Lm. CL.I. Hot galvanized steel.
710-31A-235-K2	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 12W/830/2121Lm. CL.II. Hot galvanized steel.
710-31A-245-K2	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 12W/840/2121Lm. CL.II. Hot galvanized steel.
710-31A-535	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 12W/830/2121Lm. CL.I. Anthracite RAL7016.
710-31A-545	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 12W/840/2121Lm. CL.I. Anthracite RAL7016.
710-31A-535-K2	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 12W/830/2121Lm. CL.II. Anthracite RAL7016.
710-31A-545-K2	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 12W/840/2121Lm. CL.II. Anthracite RAL7016.
710-31A-935	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 12W/830/2121Lm. CL.I. Black RAL9005.
710-31A-945	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 12W/840/2121Lm. CL.I. Black RAL9005.
710-31A-935-K2	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 12W/830/2121Lm. CL.II. Black RAL9005.
710-31A-945-K2	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 12W/840/2121Lm. CL.II. Black RAL9005.
710-31A-C35	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 14W/830/2121Lm. CL.I. Cor-ten.
710-31A-C45	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 14W/840/2121Lm. CL.I. Cor-ten.
710-31A-C35-K2	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 14W/830/2121Lm. CL.II. Cor-ten.
710-31A-C45-K2	GADO bollard fitting excl TOWER pole. FF-LED 610mA. 14W/840/2121Lm. CL.II. Cor-ten.
Accessories:	
890-701-200	TOWER pole 0,70M w/mounting hatch. 145/220mm. CL.II. Hot galvanized steel.
890-701-500	TOWER pole 0,70M w/mounting hatch. 145/220mm. CL.II. Anthracite RAL7016.
890-701-900	TOWER pole 0,70M w/mounting hatch. 145/220mm. CL.II. Black RAL9005.
890-701-C00	TOWER pole 0,70M w/mounting hatch. 145/220mm. CL.II. Cor-ten.
890-981-200	TOWER pole 0,98M w/mounting hatch. 145/220mm. CL.II. Hot galvanized steel.
890-981-500	TOWER pole 0,98M w/mounting hatch. 145/220mm. CL.II. Anthracite RAL7016.
890-981-900	TOWER pole 0,98M w/mounting hatch. 145/220mm. CL.II. Black RAL9005.
890-981-C00	TOWER pole 0,98M w/mounting hatch. 145/220mm. CL.II. Cor-ten.
920-650-200	TOWER foundation f/burial. 190x190x500mm. Hot galvanized steel.

Note: For lumens out of the luminaire, see Photometric Data on the website.

Variation options:

- Possibility of project-adapted configuration.
- Available with other lenses on request.

Key features:

- CL. II is prepared for security efforts.
- 10 year anti-corrosion warranty.
- 10 year reorder warranty.
- 5 year LED og driver warranty.
- Life expectancy 50.000 hours.
- Integrated >10 kV surge protection.

