

Art.Nr.	Type
634-22A-235-K2	DeKaLED G5 park fitting. Fortimo DLM ES 18W/830/2000Lm. CL.II. Hot galvanized steel.
634-22A-245-K2	DeKaLED G5 park fitting. Fortimo DLM ES 18W/840/2000Lm. CL.II. Hot galvanized steel.
634-22A-535-K2	DeKaLED G5 park fitting. Fortimo DLM ES 18W/830/2000Lm. CL.II. Anthracite RAL7016.
634-22A-545-K2	DeKaLED G5 park fitting. Fortimo DLM ES 18W/840/2000Lm. CL.II. Anthracite RAL7016.
634-22A-935-K2	DeKaLED G5 park fitting. Fortimo DLM ES 18W/830/2000Lm. CL.II. Black RAL9005.
634-22A-945-K2	DeKaLED G5 park fitting. Fortimo DLM ES 18W/840/2000Lm. CL.II. Black RAL9005.
634-23A-235-K2	DeKaLED G5 park fitting. Fortimo DLM ES 27W/830/3000Lm. CL.II. Hot galvanized steel.
634-23A-245-K2	DeKaLED G5 park fitting. Fortimo DLM ES 27W/840/3000Lm. CL.II. Hot galvanized steel.
634-23A-535-K2	DeKaLED G5 park fitting. Fortimo DLM ES 27W/840/3000Lm. CL.II. Anthracite RAL7016.
634-23A-545-K2	DeKaLED G5 park fitting. Fortimo DLM ES 27W/840/3000Lm. CL.II. Anthracite RAL7016.
634-23A-935-K2	DeKaLED G5 park fitting. Fortimo DLM ES 27W/840/3000Lm. CL.II. Black RAL9005.
634-23A-945-K2	DeKaLED G5 park fitting. Fortimo DLM ES 27W/840/3000Lm. CL.II. Black RAL9005.
Accessories:	
800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
920-67-6342-12	Cover screen 120°. Hot galvanized plate.
920-67-6342-18	Cover screen 180°. Hot galvanized plate.

	DeKaLED G5	DeKaLED street
Driver	230V LED module. No driver.	Philips Xitanium series
Operating hours driver	No driver	min. 100.000 hrs
LED module	Philips LED DLM EaseSelect	Philips LED SLM
Operating hours LED	min. 50.000 hrs	min. 100.000 hrs
Surge protection	No	6/8 kV
Dimming	No	Yes. Multiple options.
Light distribution	Symmetric	Symmetric (RSM) Asymmetric (ASM)

Variation options:

- Possibility of project-adapted configuration.

Key features:

- 10 year anti-corrosion warranty. (Hot galvanized)
- 10 year reorder warranty.
- 5 year LED og driver warranty.
- Supplied with 5M cable.
- For top mounting on Ø60mm pole.

