

Art.Nr.	Type
635-2AS-2401-K2	DeKaLED street park fitting. Fortimo SLM 24W/840/3500Lm ASM ON/OFF. CL.II. Hot galvanized steel.
635-2AS-2402-K2	DeKaLED street park fitting. Fortimo SLM 24W/840/3500Lm ASM 50% 22-06. CL.II. Hot galvanized steel.
635-2AS-5401-K2	DeKaLED street park fitting. Fortimo SLM 24W/840/3500Lm ASM ON/OFF. CL.II. Anthracite RAL7016.
635-2AS-5402-K2	DeKaLED street park fitting. Fortimo SLM 24W/840/3500Lm ASM 50% 22-06. CL.II. Anthracite RAL7016.
635-2AS-9401-K2	DeKaLED street park fitting. Fortimo SLM 24W/840/3500Lm ASM ON/OFF. CL.II. Black RAL9005.
635-2AS-9402-K2	DeKaLED street park fitting. Fortimo SLM 24W/840/3500Lm ASM 50% 22-06. CL.II. Black RAL9005.
635-2RS-2401-K2	DeKaLED street park fitting. Fortimo SLM 24W/840/3500Lm RSM ON/OFF. CL.II. Hot galvanized steel.
635-2RS-2402-K2	DeKaLED street park fitting. Fortimo SLM 24W/840/3500Lm RSM 50% 22-06. CL.II. Hot galvanized steel.
635-2RS-5401-K2	DeKaLED street park fitting. Fortimo SLM 24W/840/3500Lm RSM ON/OFF. CL.II. Anthracite RAL7016.
635-2RS-5402-K2	DeKaLED street park fitting. Fortimo SLM 24W/840/3500Lm RSM 50% 22-06. CL.II. Anthracite RAL7016.
635-2RS-9401-K2	DeKaLED street park fitting. Fortimo SLM 24W/840/3500Lm RSM ON/OFF. CL.II. Black RAL9005.
635-2RS-9402-K2	DeKaLED street park fitting. Fortimo SLM 24W/840/3500Lm RSM 50% 22-06. CL.II. Black RAL9005.
Accessories:	
800-145-500	Insulation sleeve (foam block) Ø135/60 for poles Ø133/Ø108mm.
920-67-6342-12	Cover screen 120°. Hot galvanized plate.
920-67-6342-18	Cover screen 180°. Hot galvanized plate.

	DeKaLED G5	DeKaLED street
Driver	230V LED module. No driver.	Philips Xitanium series
Operating hours driver	No driver	min. 100.000 hrs
LED module	Philips LED DLM EaseSelect	Philips LED SLM
Operating hours LED	min. 50.000 hrs	min. 100.000 hrs
Surge protection	No	6/8 kV
Dimming	No	Yes. Multiple options.
Light distribution	Symmetric	Symmetric (RSM) Asymmetric (ASM)

Variation options:

- Possibility of project-adapted configuration.

Key features:

- 10 year anti-corrosion warranty. (Hot galvanized)
- 10 year reorder warranty.
- 5 year LED og driver warranty.
- Supplied with 5M cable.
- For top mounting on Ø60mm pole.

