



Commercial Oil

Cleaning and oiling in a single workflow

Commercial Oil is for use in high traffic areas, where deep cleaning and oiling of the wood is required, in a single process. The oil is quick drying and therefore ideal for buildings such as airports, railway stations and public areas where it is not possible to seal off an area for an extended period of time. Commercial Oil cleans and maintains the wood thoroughly, leaving a surface that is both water-repellent and maintained.

- Simple workflow - Timesaving
- Easy application and quick-drying
- For high traffic areas
- Re-oils and protects the wood

Application area

For cleaning, oiling and care of previously oiled wood floors.

Work description

Preparation

It is important that the product, the room and the floor are at a temperature between 15°C and 30°C and that air humidity is approx. 50 %. Wood humidity must not exceed 12%. Make sure that the room is well-ventilated for optimal evaporation and drying time. If the surface is very dirty and stained, we recommend cleaning with WOCA Intensive Wood Cleaner, diluted 1:20 using a buffing machine and green polishing pad before the first application of Commercial Oil.

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

Thoroughly shake the container of Commercial Oil, both before and during use. Apply the oil using a buffing machine and a green polishing pad. The oil should be polished well into the wood. The surface must not appear wet afterwards.

Please note

For regular cleaning, use WOCA Commercial Soap for example every 2 or 3 days. Follow dosage instructions on the label. The soap is suitable for use in floor washing machines. Commercial Oil should be applied 2-4 times a year, or as required.

Drying time

Light use: 2-3 hours at 20°C

Recommendation: Do not expose the floor to water or clean it for the first 24 hours, while the oil is hardening. After 24 hours the floor can be cleaned with WOCA Commercial Soap, which gives the surface extra protection.

Fully hard: 24 hours at 20°C

Technical data

VOC: 0 g/l, maximum VOC content (A/f (SB)): 700 g/l.

Density: 0.80-0.85 g/ml.

Shelf life: 3 years

Application Temperature: +15-30°C and approx. 50% air humidity.

Coverage: 100 m²/L

Cleaning of tools: Use WOCA Solvent or turpentine

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight).
Store frost-free during winter and cool during summer.

Viscosity: 10-15 Sec. DIN Cup 4

Solid content: 10-20%

Mixing ratio: Ready to use. Do not dilute.

Maintenance and related products

Maintaining and cleaning

For regular cleaning, use WOCA Commercial Soap.

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.