Industrial Oil

Basic industrial oxidizing oil for wooden floors

Industrial Oil 1502 is a fast air-drying wood finish based on natural vegetable oils with high penetration, ensuring a durable wood floor combined with an effective and flexible application process. The oil is used for basic treatment of floors

- Fast air-drying oil
- Easy handling in the production

Application area

For treatment of wooden floors, parquets, wall panels and ceiling panels in hardwood and softwood.

Work description

Preparation
The wood must be clean, dry and free from dust.

Sanding grits
Grit 100-120.

Intermediate sanding grits
Grit 320-400.

Please note
Viscosity correction: Correction can be made with WOCA Solvent only, #328575I.
Industrial oil No1 or Industrial Hardwax oil 1505 can be used as topcoat for Industrial oil 1502

How to apply

The product must be stirred before and during application.

Application method:
Roller coater, Nitrile or natural rubber, shore 20-30.

Number of coats:
The oil may be applied on one or two roller stations.

Application amount:
Depends on the type of wood:
Hardwood: approx. 25-30 gr/m2. Softwood: approx. 40 gr/m2.
Second coat: approx. 10 gr/m2 after 8 hours of drying.

Note:
Quantities are only recommendations and may vary.

Drying time

Fully hard : 7 days at 20°C

Technical data

VOC: 500 g/l, maximum VOC content (A/f (SB)): 700 g/l.

Density: 0.90-0.95 g/ml.

Shelf life: 3 years

Coverage: 25-40 m²/L

Colours: Natural

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 20 L

Viscosity: 20-25 Sec. DIN Cup 4

Solid content: 50-55%

Maintenance and related products

Maintaining and cleaning
The industrial surface treatment can be maintained with WOCA maintenance products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.