Master Colour Oil



Oiling of wooden floors

Master Colour Oil provides beautiful colour and durable protection in a single treatment. It enhances the natural grain and character of the wood, protects against water and dirt, and can be overcoated with lacquer if required.

- Gives color and protection in one treatment
- Highlights the natural structure and appearance of the wood
- Creates a durable surface with high durability
- Effectively protects against water and dirt
- Can be overcoated with lacquer for enhanced protection and greater flexibility

Application area

For untreated, new or newly-sanded wooden surfaces.

Work description

Preparation
Product, room and floor temperature must be between 15-30°C. Wood humidity must not exceed 12%. Ensure good ventilation during application and when drying. The wood must be newly sanded, use grit 100-120 for the final sanding. Vacuum thoroughly. Clean the wood with WOCA Intensive Wood Cleaner and leave it to dry for at least 8 hours before applying the oil.

Always Remember
Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Final sanding
Grit 100-120.

Treatment
Thoroughly shake the container of Master Colour Oil, both before and during use. Containers with different batch numbers should be mixed to avoid colour mismatch. Apply the oil using a short-bristled paint roller (4-6 mm) in an even coat. Work in small areas of no more than 10 m² at a time. Leave the oil to soak in for 10-20 min. If the oil soaks quickly into the wood, apply more oil. Polish the oil into the wood until the surface appears saturated. Use a buffing machine with a beige pad for large areas and a polishing cloth/pad manually for small areas. Remove excess oil with dry, lint-free cotton cloths or pads until the surface no longer appears wet. Continue until the whole area has been polished and excess oil has been thoroughly removed. To ensure a good saturation the surface should be re-polished with 1 dl Master Colour Oil per 10 m2 within 6-12 hours after the first application. The oil should be polished thoroughly, as described earlier.

Please note
Do not expose the surface to water or clean it for the first 7 days while the oil is hardening. After 7 days the floor can be cleaned with WOCA Natural Soap, which gives the surface extra protection.

Drying time

Drying time : 12-24 hours at 20°C

Fully hard : 7 days at 20°C

Technical data

VOC: 140 g/l, maximum VOC content (A/i (SB)): 500 g/l.

Density: 0.90-0.95 g/ml.

Shelf life: 3 years

Application Temperature: +15-25°C and approx. 50% air humidity.

Coverage: 10-12 m²/L

Colours: Natural, White, Brazil Brown, Castle Grey, Extra White, Walnut, Black

Cleaning of tools: Use WOCA Solvent or turpentine

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 750 ml - 2.5 L - 5 L

Dilution: WOCA Solvent (does not normally need to be diluted).

Solid content: 50-55%

Maintenance and related products

Maintaining and cleaning
For daily cleaning, WOCA Natural Soap is recommended, which effectively washes and cares for the wood. Supplement occasionally with WOCA Oil Refreshing Soap, which also adds a little oil to the wood with each wash. Maintain with Maintenance Oil or Maintenance Gel as needed.

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.