Worktop Kit

Oils and protects wooden countertops and furniture



WOCA Worktop Kit is developed for the treatment and maintenance of countertops and other indoor wooden surfaces. Worktop Oil penetrates deeply into the wood and provides a durable, water- and dirt-repellent surface while enhancing the wood's natural color and structure. The oil is approved for contact with food and can be used on untreated, newly sanded, and previously oil-treated surfaces. The kit contains 0.75 L Worktop Oil, 250 ml Intensive Wood Cleaner, black sanding pad, white polishing pad, lint-free cloth, gloves, and a user manual.

- Everything you need - in a box
- Approved for contact with food (Glass & Fork)
- Contains natural oils
- Provides a dirt and water-repellent surface
- Can be used on all types of wood
- Highlights the wood's natural glow and structure

Application area

For the care and maintenance of untreated or previously oil-treated/sanded surfaces such as worktops, tabletops and kitchen furnitures. Only for indoor use.

Work description

Treatment
0

Please note
Wood humidity must not exceed 18%. High temperature and low air humidity will reduce drying times. Low temperature and high air humidity will extend drying times. The worktop should be maintained at least once a year, or when necessary. For a superior result, use Worktop Oil or WOCA Maintenance Gel. For a more thorough restoration, follow the entire procedure.

Drying time

Between coats : 30-60 minutes at 20°C

Light use : 24 hours at 20°C

Recommendation : The moisture content of the wood must not exceed 18%. Note that high temperature and low humidity shorten the drying time, while low temperature and high humidity extend it.

Fully hard : 7 days at 20°C

Technical data

Declaration: Less than 5%: non-ionic surfactants, cationic surfactants.

VOC: 295 g/l, maximum VOC content (A/i (SB)): 500 g/l.

Density: 0.90-0.95 g/ml.

Shelf life: 3 years

Application Temperature: +15-30°C and approx. 50% air humidity.

Coverage: 12-15 m²/L

Colours: Natural

Cleaning of tools: Use WOCA Solvent or turpentine

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 1 L

Viscosity: 30-35 Sec. DIN Cup 4

Odour: Characteristic

Solid content: 70-75%

Maintenance and related products

Maintaining and cleaning
Cleaning: For daily cleaning, use WOCA Natural Soap or WOCA Natural Soap Spray.
Maintenance: The countertop is maintained as needed with WOCA Worktop Oil or WOCA Maintenance Gel.

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.