Oil Care



Water-based revitaliser for oil-treated wood

Oil Care is a waterbased and indoor climate friendly maintenance oil that can be used on all oiled wood surfaces, oxidating as well as UV-/factory-oiled, and is especially suitable for the regular maintenance of oiled wood floors.

- Simple application both manually and by machine
- Fast-drying
- Water-based maintenance product
- Indoor climate certified

Application area

For all oiled wood surfaces - whether they are finished with oxidative oil or UV oil (factory-oiled). Oil Care Natural is suitable for dark wood species, whereas Oil Care White is used for lighter, possibly lye treated wood such as pine, ash or oak, in order to preserve and enhance the light look.

Work description

Preparation
Clean the floor with Intensive Wood Cleaner mixed into water. Leave the floor to dry for at least 8 hours. The floor must be completely dry befor treatment. Product, room and floor temperature should be between 15-30°C. Ensure good ventilation at all times during the application and drying time.

Always Remember
Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment
Shake the container carefully. Polish in a thin layer of the Oil Care with a white pad, cotton cloth or use polishing machine for large surfaces. It is important that the Oil Care is carefully polished into the wood. Continue polishing until the wood appears saturated and the surface looks uniform. The floor should not appear wet and there should not be any excess oil left on the surface after polishing. Work in smaller areas one step at a time until the floor is finished.

Drying time

Drying time : 12-24 hours at 20°C

Light use : 3-4 hours at 20°C

Recommendation : Do not expose the floor to water during hardening time.

Fully hard : 3 days at 20°C

Technical data

VOC: 10 g/l, maximum VOC content (A/i (WB)): 140 g/l.

Density: 0.95-1.00 g/ml.

pH-value: pH 8-9

Shelf life: 3 years

Application Temperature: +15-30°C and approx. 50% air humidity.

Coverage: 30-40 m²/L

Colours: Natural, White

Cleaning of tools: Use soap and water

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 1 L

Viscosity: 20-25 Sec. DIN Cup 4

Odour: Faint

Solid content: 10-20%

Mixing ratio: Ready to use. Do not dilute.

Maintenance and related products

Maintaining and cleaning
For daily cleaning, WOCA Natural Soap is recommended, which effectively washes and cares for the wood. Supplement occasionally with WOCA Oil Refreshing Soap, which also adds a little oil to the wood with each wash.

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.