

# Furniture Care Kit, Oil



## For refreshing of oiled furniture

Wood Furniture Care Kit, Oil is used for refreshing of oiled wood furniture so they stay beautiful for many years. It cares for and refreshes the wood, giving your furniture an attractive and durable oil-treated surface. The kit contains all you need for the entire treatment: 200 ml Maintenance Gel, 1L Intensive Wood Cleaner, a black sanding pad, a white polishing pad, a lint-free cloth and work instructions.

- All you need - in one box
- Provides a water- and dirt-resistant surface
- Refreshes the natural glow of the wood
- Safe for food contact
- Easy to apply
- Quick-drying

## Application area

For refreshing of oiled furniture. Furniture Kit gives a durable and beautiful look and the gel is safe for food contact, is fast-drying and has a high resistance to stains. The oil can be applied on many types of wood, e.g. oak, beech, ash, walnut and mahogany. Contains linseed. Only for indoor use.

## Work description

### Preparation

Prior to treatment with Maintenance Gel, the wood surface must be cleaned thoroughly. Clean the surface with Intensive Wood Cleaner (mixed 1:20) and leave it for 5 minutes. Wipe the surface with a clean cloth that has been wrung out in clean water. The furniture should dry for at least 8 hours at 20°C. If the surface has become uneven (grainraise), the wood can be sanded with the black sanding pad (gritt 240-400). Remove sanding residue using the small brush head of your vacuum cleaner.

### Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

### Treatment

Apply an appropriate amount of Maintenance Gel to the white hand scrubber, not directly onto the wood. Carefully rub the gel into the wood in small circular movements. It is important to treat the entire surface until the wood is entirely saturated. We recommend that you apply the gel to smaller areas, as the product dries quickly. Wipe off excess gel using a lint-free cloth. No excess gel should remain on the surface. Wait 4-6 hours before using the treated item. Avoid getting water or dirt on the treated surface for the next 2-3 days.

### Please note

For daily cleaning, use a tightly wrung cloth with WOCA Natural Soap or WOCA Natural Soap, Spray. When used on UV-oiled surfaces, make sure to do a more thorough final polishing to remove all excess gel.

## Drying time

**Drying time:** 12-24 hours at 20°C

**Between coats:** 4-6 hours at 20°C

**Light use:** 4-6 hours at 20°C

**Recommendation:** The oiled surface should not be exposed to water for the first 2-3 days, as this can cause stains and discoloration. Wood humidity must not exceed 18%. High temperature and low air humidity will shorten drying times. Low temperature and high air humidity will extend drying times.

**Fully hard:** 3 days at 20°C

**Re-treatment:** Repeat the oil treatment when required.

## Technical data

**Density:** 0.90-0.95 g/ml.

**Shelf life:** 3 years

**Application Temperature:** +15-25°C and approx. 50% air humidity.

**Coverage:** Regular maintenance: 20-30 m<sup>2</sup>/200 ml. Newly-sanded/non-maintained wood: 4-6 m<sup>2</sup>/200 ml.

**Colours:** Natural

**Cleaning of tools:** Use turpentine

**Storage:** +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

**Packaging:** 1 L

**Odour:** Faint

**Solid content:** 85-90%

**Mixing ratio:** Ready to use. Do not dilute.

## Maintenance and related products

### Maintaining and cleaning

For daily cleaning, WOCA Natural Soap is recommended, which effectively washes and cares for the wood. Supplement occasionally with WOCA Oil Refreshing Soap, which also adds a little oil to the wood with each wash.

WOCA Denmark A/S  
Tværvej 6  
DK - 6640 Lunderskov  
+45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*