



# UV Oil 510

## 100 % UV-oil for wooden floors with low gloss and good penetration

UV-Oil 510 is a 100 % UV-oil that soaks deeply into the wood, creating hard-wearing wood floors with low gloss. Using this oil ensures fast production speeds as the proven UV-technology dries and cures instantly and allows immediate packing at the end of the production line. Wooden floors finished with this oil do not require additional on-site treatment after installation.

- Fast production speeds
- Ensures UV-oiled floors that are ready for use
- Low gloss

### Application area

For surface treatment of wooden floors and parquets in hardwood and softwood.

### Work description

#### Intermediate sanding grits

Grit 320-400.

#### Sanding grits

Grit 100-120.

#### Treatment

0

### Drying time

**Drying time:** UV drying with Hg lamps, min. 600-800 mJ/cm<sup>2</sup> for each lamp. Production speed 10 m/min. For pigmented systems, a combination of Gallium and Mercury lamps are preferred.

**Fully hard:** Immediately after UV-drying

### Technical data

**Density:** 1.10-1.20 g/ml.

**Shelf life:** 3 years

**Coverage:** 30-40 m<sup>2</sup>/L

**Colours:** Natural

**Storage:** +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

**Packaging:** 10 liters

**Viscosity:** 40-45 Sec. DIN Cup 4

**Solid content:** 95-100%

## Maintenance and related products

WOCA Denmark A/S  
Tværvej 6  
DK - 6640 Lunderskov  
+45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*