

Fast Filler



For manual filling of knotholes in wood

Fastfiller is used for efficient and durable repairs of cracks and knotholes in wood prior to finishing. It bonds tightly to the wood, is easy to sand, cures fast and does not shrink or crack. The filler is powder-based and designed to accept stains, oils, wax and lacquers very fast and naturally, creating a uniform and natural look. Fastfiller is an environmentally friendly product based on pure natural raw materials, 90 % animal proteins and mineral components, and it must be mixed with water before use.

- Quick-drying
- Easy to sand
- Does not shrink
- Must be treated afterwards with WOCA products

Application area

For the repair of cracks, knotholes and other holes in all types of wood.

Work description

Preparation

Mix the filler with cold water in the ratio: 1 part of water to 3-4 parts of filler. Stir the mixture to a firm and homogeneous filler and apply it directly to the wood. (The mixture must be so firm that it stays on the putty knife). It is possible to work with the mixture for approx. 30 minutes. Do not mix more filler than necessary.

Intermediate sanding grits

Grit 120-180.

Sanding grits

Grit 60-80.

Treatment

0

Please note

Viscosity correction: A very small amount of water may be added to the mixture once or twice during the work process.

Drying time

Drying time: 30-60 minutes at 20°C

Technical data

Density: 2.40-2.60 g/ml.

pH-value: pH 7-8

Shelf life: 3 years

Colours: Smoked oak

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging: 20 liters

Viscosity: 35-40 Sec. DIN Cup 4

Solid content: 95-100%

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.