Panel White



Whitening of ceilings and panels

Panel White is a water-based product for the intensive white look for wood ceilings and wall panels. Panel White is a water-based, indoor climate certified product that preserves the natural structure of the wood.

- Intensive white look for wood ceilings and wall panels
- Preserves the natural structure of the wood
- Easy to apply
- Indoor climate certified

Application area

For lightening of any type of unfinished or lacquered panels, doors and door frames made of softwood or light coloured types of wood. Panel White is used indoors for untreated and lacquered softwood. Not suitable for wood floors.

Work description

Preparation
The wood must be clean and completely dry. Wash with Intensive Wood Cleaner mixed with water and wipe off with clean water afterwards. It is recommendable to use a hard wrung cloth. Sand glossy surfaces.

Always Remember
Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment
Stir the Panel White carefully before and during use. Buckets with different batch numbers should be mixed before use to avoid differences in shade and gloss. Apply the product with a brush in an even layer lengthwise the wood grain. Do not apply on more than 3-4 boards at the time and finish them to avoid overlaps.

Drying time

Drying time : 2-3 hours at 20°C

Surface Dry : 1-2 hours at 20°C

Fully hard : 4-5 hours at 20°C

Technical data

Declaration: Water, alkyd dispersion, pigments.

VOC: 60 g/l, maximum VOC content (A/e (WB)): 130 g/l.

Density: 1.20-1.30 g/ml.

pH-value: pH 7-8

Shelf life: 3 years

Application Temperature: +15-25°C and approx. 50% air humidity.

Coverage: 10-12 m²/L

Colours: Extra White

Cleaning of tools: Use soap and water

Storage: +10-30°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 2.5 L

Dilution: Undiluted

Odour: Faint

Maintenance and related products

Maintaining and cleaning
The treated wood surface may be cleaned with Intensive Wood Cleaner mixed with water in the ratio 1:40. It is recommendable to use a hard wrung cloth.

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.