Master TS-2K Line Marking



Line marking for sports floors

Master TS-2K Line Marking is a water-based, lacquer-based 2-component line marking developed for professional marking of lines in sports and recreational facilities. The product is specifically designed for use on lacquered wooden floors, where it provides a durable, long-lasting, and precise marking with high adhesion. Master TS Line Marking 2K is available in six standard RAL colors.

- Very strong and resistant
- For professional marking of sports floors
- Designed for use with Master TS Sportslak
- 2-component

Application area

For lacquered indoor sports floors made of wood. Available in 6 colors: Yellow (RAL 1021), Red (RAL 3000), Blue (RAL 5010), Green (RAL 6029), White (RAL 9016), Black (RAL 9017)

Work description

Preparation
Preparation of untreated and sanded floors: Apply 1 coat of WOCA Base Primer and 1-2 coats of WOCA Master TS-2K Lacquer according to the product instructions, before applying Master TS 2K Line Marking.

Treatment
0

Please note
Master TS-2K Line Marking white and yellow may require 2 coats to achieve full color coverage

Drying time

Drying time : 2-3 hours at 20°C

Between coats : 2-3 hours at 20°C

Fully hard : 5 days at 20°C

Technical data

VOC: 85 g/l, maximum VOC content (A/e (WB)): 130 g/l.

Density: 1.00-1.10 g/ml.

pH-value: pH 7-8

Shelf life: 1 year

Application Temperature: +15-25°C and approx. 50% air humidity.

Coverage: 6-10 m²/L

Colours: White, Black, Red, Yellow, Blue, Green

Cleaning of tools: Use water

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 2.5 L

Viscosity: 20-25 Sec. DIN Cup 4

Mixing ratio: 100 ml for 2,5L (1:25)

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.