

Hardwax Oil Swift



Oiling and waxing of wooden floors

Hardwax Oil Swift is a fast-drying roll-on product for wooden floors, easy to apply without the need for polishing. It combines natural oils and waxes to create a durable surface with high resistance to liquids and stains. The floor acquires a neutral appearance and a non-slip, maintenance-friendly finish, making it ideal for the initial treatment of untreated, new, or newly sanded wooden surfaces.

- Good protection against liquids such as water, coffee, tea, and red wine
- Durable and resistant to scratches and marks
- Does not need to be polished in
- High coverage

Application area

For untreated, or newly-sanded wooden surfaces, or as a topcoat on top of WOCA Master Colour Oil.

Work description

Preparation

It is important that the product, the room and the floor are at a temperature between 15 °C and 30 °C and that air humidity is approx. 50 %. Wood humidity must not exceed 12%. Make sure that the room is well-ventilated for optimal evaporation and drying time. Always remember to test on a less visible spot to check the compatibility of the wood with the oil. The floor must be free of dirt, grease, wax and sanding residue. Previously treated floors should be sanded down to bare wood with grain 100-150. Vacuum thoroughly and wipe the floor down afterwards if necessary, using a tightly-wrung water-soaked cloth.

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Final sanding

Grit 120-150.

Treatment

Hardwax Oil Swift should be stirred thoroughly before and during use. Containers with different batch numbers should be mixed to avoid colour mismatch. Apply a thin layer of oil using a short-bristled paint roller (3-4 mm) or similar, along the grain of the wood. Distribute the oil thoroughly. Leave the floor to dry for 4-5 hours. Repeat the treatment within 24 hours if another coat of oil is required. A single coat of oil is normally enough for previously-oiled surfaces. For optimal adhesion floors previously treated must be intermediate sanded using a bordeaux pad before applying a layer of Hardwax Oil.

Please note

The newly-oiled floor can be used with caution the following day and is fully hardened after 7 days under normal indoor conditions. After 7 days the floor can be cleaned with WOCA Natural Soap or WOCA Oil Refreshing Soap, which gives the surface extra protection. For optimal adhesion floors previously treated must be intermediate sanded using a bordeaux pad before applying a layer of Hardwax Oil. Workstep 2 and 3 must be repeated within 24 hours if a second layer of oil is required.

Drying time

Drying time : 4-5 hours at 20°C

Recommendation : Lower temperatures and/or higher humidity can extend drying time. Do not expose the floor to water or clean it for the first 7 days while the oil is hardening.

Fully hard : 7 days at 20°C

Technical data

VOC: 510 g/l, maximum VOC content (A/i (SB)): 500 g/l.

Density: 0.90-0.95 g/ml.

Shelf life: 3 years

Application Temperature: +15-25°C and approx. 50% air humidity.

Coverage: 20 m²/L

Colours: Colourless - Matt

Cleaning of tools: Use WOCA Solvent

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 2.5 L

Viscosity: 30-35 Sec. DIN Cup 4

Odour: Strong

Solid content: 40-50%

Maintenance and related products

Maintaining and cleaning

For daily cleaning, WOCA Natural Soap is recommended, which effectively washes and cares for the wood. Supplement occasionally with WOCA Oil Refreshing Soap, which also adds a little oil to the wood with each wash.

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.