

Neutral Lye

Priming and ligthning of wood before treatment

Neutral Lye is used for lye priming of unfinished or newly sanded interior woodwork i.e. floor, stairs, furniture and panels. The priming prevents the wood from yellowing and enhances the wood grain creating a coloured wash effect, depending on the chosen colour. Neutral Lye may be used on all types of wood.

- Provides a lighter finish
- Reduces the yellowing process of wood
- Suitable for any type of wood

Application area

To be used on new or freshly sanded wood floors. Neutral Lye may be applied on solid floors as well as on engineered floors. Neutral Lye is available in white and super white.

Work description

Preparation
The untreated wood must be sanded with fine sandpaper and be clean and dry before applying lye.

Please note
Wear suitable protective clothing, gloves and eye/face protection. Stir thoroughly before use

Drying time

Drying time : 8-10 hours at 20°C

Technical data

Declaration: >15% - <30%: Dye. < 5%: Preservative (2-BROMO-2-NITROPROPANE-1,3DIOL)

VOC: 30 g/l, maximum VOC content (A/g (WB)): 30 g/l.

Density: 0.95-1.00 g/ml.

pH-value: pH 7-8

Shelf life: 2 years

Coverage: 8-10 m²/L

Colours: Extra White

Cleaning of tools: Use warm water

Storage: +10-30°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 5 L

Odour: Faint

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.