



Industrial Lye

Minimizes yellowing of wood

Industrial Lye bleaches down lighter hardwood and minimizes the natural occurrence of the wood turning yellow. It may also be used on exotic types of wood.

- Minimizes yellowing
- Can be used on all types of wood
- Instant lightening of wood
- Must be treated afterwards with WOCA oils or WOCA lacquers
- Minimizes colour variation of the wood

Application area

For all types of untreated wood.

Work description

Intermediate sanding grits

Grit 400-500.

Sanding grits

Grit 100-120.

Treatment

0

Drying time

Technical data

Density: 1.00-1.10 g/ml.

pH-value: pH 9-10

Shelf life: 3 years

Coverage: 40-50 m²/L

Colours: White

Packaging: 30 liters

Viscosity: 10-15 Sec. DIN Cup 4

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.