



No1 Industrial Oil

High-performance industrial oxidizing oil for wooden floors

Industrial Oil No1 is a fast air-drying and high-performance wood finish based on natural vegetable oils with high penetration. The oil is extremely suitable for production of oil-finished floor solutions offering high protection and long-lasting wooden floors combined with an effective and flexible application process on the roller coater. Industrial Oil No1 is available as ready-to-use oils or as a unique mixing system called Industrial Base Colour System 4+1.

- Extreme protection of the wood
- Next level of industrial air-drying oils
- Easy and flexible handling in the production
- Ensures finished floors, ready for installation

Application area

For surface treatment of wooden floors, parquets, wall panels and ceiling panels in solid wood, hardwood and softwood.

Work description

Intermediate sanding grits

Grit 320-400.

Sanding grits

Grit 100-120.

Treatment

0

Please note

Viscosity correction: Correction can be made with WOCA Solvent only, #328575l.

Drying time

Drying time: Drying on racks or pallets. Drying is accelerated in drying tunnel with max. 40°C and good air circulation.

Fully hard: 7 days at 20°C

Technical data

Density: 0.90-0.95 g/ml.

Shelf life: 3 years

Coverage: 30-40 m²/L

Colours: Natural

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging: 10 liters

Viscosity: 40-45 Sec. DIN Cup 4

Solid content: 75-80%

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.