Wood Lye



Minimises natural yellowing of the wood

Wood Lye is used for priming of untreated or newly sanded interior woodwork like floors, stairs, furnitures and panels. The priming minimizes yellowing of the wood and highlights the wood structure creating a coloured wash effect, depending on the chosen colour. Wood Lye is suitable for all types of wood.

- Minimizes the yellowing process of the wood
- For a lighter finish
- For oil, soap, or finish
- Suitable for any type of wood

Application area

For priming of unfinished and newly sanded interior wood. Suitable for all wood species. Subsequent treatment with oil, lacquer, or soap is required.

Work description

Preparation
Ensure that the unfinished woodwork is clean, dry, and finely sanded before applying the lye.

Always Remember
Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment
Shake the container thoroughly and pour the lye into a plastic bucket. Ensure that no pigments remain in the container. Stir the lye regularly during application to prevent pigments from settling at the bottom. Apply an even coat of the lye lengthwise along the wood grain using a WOCA Applicator, nylon brush, or roller. Apply a minimum of 1 litre per 10 m² of wood. Allow the surface to dry for approximately 8–12 hours at 20 °C. Lightly de-nib raised wood fibres and remove excess pigments using a medium sanding or polishing pad (e.g. green or bordeaux). Remove sanding dust thoroughly with a vacuum cleaner. Finish the wood surface with a WOCA oil, lacquer, or soap.

Drying time

Drying time : 8-10 hours at 20°C

Technical data

Declaration: < 5%: Non-ionic surfactants. Preservative (BENZISOTHIAZOLINONE). Preservative (Methylchloroisothiazolinone/Methylisothiazolinone mixture (MCIT/MIT)

VOC: 10 g/l, maximum VOC content (A/g (WB)): 30 g/l.

Density: 1.00-1.10 g/ml.

pH-value: pH 8-9

Shelf life: 3 years

Application Temperature: +15-30°C and approx. 50% air humidity.

Coverage: 8-10 m²/L

Colours: White, Grey

Cleaning of tools: Use water

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 2.5 L

Dilution: Undiluted

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.