



Retarder for Lacquer

Prolongs the open time of lacquers

Prolongs the open time for waterbased lacquers

- For all waterbased WOCA Master lacquers
- Easy to mix
- Extends potlife

Application area

For all WOCA Master Lacquers

Work description

Preparation

Shake Retarder well before mixing into the lacquer.

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

Mix 100 ml Retarder into 5 L lacquer incl. hardener. Stir the mixture frequently during use to assure a uniform appearance. See the technical data sheet for the specific lacquer.

Technical data

VOC: 110 g/l, maximum VOC content (A/i (WB)): 140 g/l.

Density: 0.95-1.00 g/ml.

Shelf life: 3 years

Colours: Colourless

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging: 100 ml

Mixing ratio: 100 ml for 5 L (1:50)

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.