

Exterior Wood Primer



Water-based primer for highly absorbent wood

Exterior Wood Primer is a water-based primer for priming surfaces such as façades, windows, fences and carports. The product protects the wood, as well as enhancing adhesion and durability of a subsequent surface treatment. Exterior Wood Primer is very well suited for fir, accoya, larch, pine, oak and non-impregnated wood.

- Reduces cracking and deterioration of wood
- Extends the lifetime of wood
- Protects the wood against moisture
- Ideal for all softwood and vulnerable wood

Application area

For new and old wood. Very well suited for fir, accoya, larch, pine, oak and non-impregnated wood. Optimum durability is achieved by regular cleaning and correct treatment, dependign on the construction, the condition of the wood and wind and weather. Check the treated surfaces annually. Repair any damage immediately.

Work description

Preparation

Clean the surface with WOCA Exterior Wood Cleaner. The surface must be completely dry and free of dust and dirt. New wood should be treated as soon as possible. Can also be used as a pre-treatment for previously oiled wood that has been weathered. The treatment with Exterior Wood Primer must be performed in dry weather, at a temperature between 15-30° C. Avoid direct sunlight and intense heat. Wood humidity must not exceed 17%.

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

Shake the container well. Apply Exterior Wood Primer undiluted, with a brush or roller. It is important that the product is applied thoroughly and evenly. Start with the end sections of the wood. Leave the wood to dry for at least 24 hours before treatment.

Please note

Exterior Wood Primer is a pre-treatment product, so the surface must then be treated with WOCA Exterior Wood Oil within 14 days. Make sure that you have properly sealed the container after use. Check the treated surfaces annually. Repair any damage immediately.

Drying time

Drying time : 24 hours at 20°C

Technical data

VOC: 10 g/l, maximum VOC content (A/g (WB)): 30 g/l.

Density: 1.00-1.10 g/ml.

Shelf life: 3 years

Application Temperature: +15-30°C and approx. 50% air humidity.

Coverage: 10-15 m²/L

Colours: Natural

Cleaning of tools: Use warm water

Storage: +5-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 2.5 L

Viscosity: 15-20 Sec. DIN Cup 4

Moisture content: The moisture content of the wood must not exceed 17%.

Odour: Faint

Solid content: 10-20%

Mixing ratio: Ready to use. Do not dilute.

Maintenance and related products

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.