



Driftwood Lye

Gives oak a weather-beaten patina

Driftwood Lye is a unique, water-based product, which gives the wood a weather-beaten patina. The product is primarily for oak wood. By using this product, the wood will get a very nice two-dimensional design. Finally, the surface must be treated with one of the WOCA oils.

- Gives oak a weather-beaten patina
- Creates unique colour solutions
- Water-based
- Reacts with tannin in the wood - suitable for oak wood

Application area

Used for priming of oak wood. Creates a unique colour and weather-beaten patina.

Work description

Preparation

The unfinished woodwork must be clean, dry and finely sanded (grit 100-120) before applying the lye.

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

Shake the container well and pour the lye into a plastic bucket. It is important that no pigments are left in the container. Stir regularly during the application to prevent the pigments from settling to the bottom. Apply an even coat of the lye with the WOCA Applicator, a nylon brush or roller lengthwise along the grain. Apply at least 1 L of lye per 10 m² of wood. Leave wood to dry for approx. 8-12 hours at 20°C. De-nib standing fibres and remove excess pigments with a medium e.g. green or bordeaux, sanding polishing pad. Remove the sanding dust with a vacuum cleaner. Finish the wood surface with a WOCA oil.

Drying time

Drying time: 6-12 hours at 20°C

Technical data

VOC: 10 g/l, maximum VOC content (A/g (WB)): 30 g/l.

Density: 1.10-1.20 g/ml.

pH-value: pH 13-14

Shelf life: 3 years

Application Temperature: +15-30°C and approx. 50% air humidity.

Coverage: 8-10 m²/L

Colours: White, Grey

Cleaning of tools: Use water

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging: 2.5 L

Dilution: Undiluted

Odour: Characteristic

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.