

# Industrial Oil 2000



## Coming soon

### Fast-drying industrial oxidizing oil for wooden floors

Industrial Oil 2000 is a fast air-drying oil with high solid content and high penetration. It is very receptive to coloured pigments, allowing the creation of exceptionally powerful colours, and is ideal for creation of customized colour solutions in combination with stains. The oil is based on natural vegetable oils and ensures a durable wood floor combined with an effective and flexible roller coater application.

- Fast air-drying oil
- Endless choices of customized colours
- Easy application on a variety of processes
- Generates well-tested durable wooden floors

#### Application area

For surface treatment of wooden floors and parquets in solid wood, hardwood and softwood.

#### Work description

Intermediate sanding grits

Grit 320-400.

Sanding grits

Grit 100-120.

**Treatment** 

0

Please note

Viscosity correction: Correction can be made with WOCA Solvent only, #3285751.

### Drying time

Drying time: Drying on racks or pallets. Drying is accelerated in drying

tunnel with max. 40°C and good air circulation.

Fully hard: 7 days at 20°C

#### Technical data

Density: 0.90-0.95 g/ml.

Shelf life: 3 years

Coverage: 25-40 m<sup>2</sup>/L

Colours: Natural

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g.

sunlight). Store frost-free during winter and cool during summer.



Solid content: 65-70%

### Maintenance and related products

WOCA Denmark A/S Tværvej 6 DK - 6640 Lunderskov +45 9958 5600 info@wocadenmark.com wocadenmark.com This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.