Industrial Oil 2000

Fast-drying industrial oxidizing oil for wooden floors



Industrial Oil 2000 is a fast air-drying oil with high solid content and high penetration. It is very receptive to coloured pigments, allowing the creation of exceptionally powerful colours, and is ideal for creation of customized colour solutions in combination with stains. The oil is based on natural vegetable oils and ensures a durable wood floor combined with an effective and flexible roller coater application.

- Fast air-drying oil
- Endless choices of customized colours
- Easy application on a variety of processes
- Generates well-tested durable wooden floors

Application area

For surface treatment of wooden floors and parquets in solid wood, hardwood and softwood.

Work description

Preparation
The wood must be clean, dry and free from dust.

Sanding grits
Grit 100-120.

Intermediate sanding grits
Grit 320-400.

Please note
Viscosity correction: Correction can be made with WOCA Solvent only, #328575I.

How to apply

The product must be stirred before and during application.

Application method:
Roller coater, Nitrile or natural rubber, shore 20-30.

Number of coats:
The oil may be applied on one or two roller stations.

Application amount:
Depends on the type of wood:
Hardwood: approx. 25-30 gr/m2. Softwood: approx. 40 gr/m2.
Second coat: approx. 10 gr/m2 after 8 hours of drying.

Note:
Quantities are only recommendations and may vary.

Drying time

Fully hard : 7 days at 20°C

Technical data

VOC: 235 g/l, maximum VOC content (A/f (SB)): 700 g/l.

Density: 0.90-0.95 g/ml.

Shelf life: 3 years

Coverage: 25-40 m²/L

Colours: Dark grey

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 10 L

Viscosity: 25-30 Sec. DIN Cup 4

Solid content: 65-70%

Maintenance and related products

Maintaining and cleaning
The industrial surface treatment can be maintained with WOCA maintenance products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.