

# Tropical Filler

## For filling gaps, knots and cracks in wood manually

Tropical Filler is a high-quality environmentally-friendly powder-based filler that is easy to mix. It has the same qualities as the old WOCA Wood Filler, however the Tropical Filler is adjusted to fit the tropical climate (high humidity areas i.e. 80 %), but can also be used in areas with lower humidity. It is suitable for various types of repairs in wood and is applicable for wood repairs with a depth up to 15 mm. You can mix and match the different colours as you wish, but it is also possible to add colour pigment or stain to the mixture to obtain a customized colour. There is no expiration date on the raw powder if it is properly protected from moisture, water and foreign objects.



- Can be surface treated with both stain, lacquer, UV- and oxidizing oil
- Offers a countless number of colour options
- Made of natural raw materials

## Application area

For use on furniture and floorings. Suitable for all types of wood, solid as well as veneered surfaces. Only for indoor use.

## Work description

### Preparation

Mix the filler with cold water in the ratio: 1-1,5 parts of water to 3 parts of filler. Stir the mixture to a firm and homogeneous filler and apply it directly to the wood. (The mixture must be so firm that it stays on the putty knife). It is possible to work with the mixture for approx. 45 minutes. Do not mix more filler than necessary.

### Sanding grits

Grit 60-80.

### Please note

Viscosity Correction: A small amount of water may be added to the mixture within the first 5 minutes, if needed.

## How to apply

Mix the filler with cold water in the ratio: 1-1.5 parts of water to 3 parts of filler. The mixture must be uniform before use. It is possible to work with the mixture for approx. 45 min.

### Note:

Hardener for Fast/Tropical Filler can be added to the water before mixing for improved strength of the filler and for wire brushing filled holes. See separate TDS.

## Technical data

**VOC:** 0 g/l, maximum VOC content (A/e (SB)): 400 g/l.

**Density:** 2.40-2.60 g/ml.

**pH-value:** pH 7-8

**Shelf life:** 3 years

**Storage:** +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

**Specific gravity:** 2.20-2.40 g/ml.

**Solid content:** 95-100%

## Maintenance and related products

### Maintaining and cleaning

The industrial surface treatment can be maintained with WOCA maintenance products

WOCA Denmark A/S  
Tværvej 6  
DK - 6640 Lunderskov  
+45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*