



Solvent for Oxidizing Oils

Thinner used for oxidative oils

Solvent for Oxi Oils is used for thinning and reducing viscosity of oxidizing oils. It helps maximizing productivity by optimizing the viscosity of the oils to suit the machines.

- Very efficient thinning of oxidizing oils
- Easy to use

Application area

Used for thinning of oxidative oils.

Work description

Treatment
0

Drying time

Technical data

Density: 0.80-0.85 g/ml.

Shelf life: 3 years

Colours: Colourless

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging: 25 liters

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.