

SAFETY DATA SHEET

# Master Multi Primer

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

*Trade name:* Master Multi Primer  
*Product no.:* 197000  
*Unique formula identifier (UFI):* P440-Q0D5-M00N-KDWQ

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

*Relevant identified uses of the substance or mixture:* None known.  
*Uses advised against :* None known.

### 1.3. Details of the supplier of the safety data sheet

*Company and address:* **WOCA Denmark A/S**  
Tværvej 6  
6640 Lunderskov  
Denmark  
+45 9958 5600

*Contact person:* WOCA Denmark  
*E-mail:* info@wocadenmark.com  
*Revision:* 15/04/2026  
*SDS Version:* 1.0

### 1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)  
General public:  
England - Dial 111 to reach NHS 111 (24 hour service)  
Scotland - Dial 111 to reach NHS 24 (24 hour service)  
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)  
See section 4 "First aid measures".

## SECTION 2: HAZARDS IDENTIFICATION

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

### 2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.  
Eye Irrit. 2; H319, Causes serious eye irritation.

## 2.2. Label elements

*Hazard pictogram(s):*



*Signal word:*

Danger

*Hazard statement(s):*

Highly flammable liquid and vapour. (H225)  
Causes serious eye irritation. (H319)

*Precautionary statement(s):*

*General:*

If medical advice is needed, have product container or label at hand. (P101)  
Keep out of reach of children. (P102)

*Prevention:*

Wash hands thoroughly after handling. (P264)  
Wear eye protection. (P280)

*Response:*

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)  
If eye irritation persists: Get medical advice/attention. (P337+P313)

*Storage:*

Store in a well-ventilated place. Keep cool. (P403+P235)

*Disposal:*

Dispose of contents/container in accordance with local regulation. (P501)

*Hazardous substances:*

Contains no substances that need to be listed on the label.

*Additional labelling:*

UFI: P440-Q0D5-M00N-KDWQ

## 2.3. Other hazards

*Additional warnings:*

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

Not applicable. This product is a mixture.

### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Ethanol	CAS No.: 64-17-5 EC No.: 200-578-6 UK-REACH: 01-2119457610-43-XXXX	80-95%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 (SCL: 50.00 %)	

	Index No.: 603-002-00-5			
Propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 UK-REACH: 01-2119457558-25-XXXX Index No.: 603-117-00-0	10-15%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

## Other information

-

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

*General information:*

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

*Inhalation:*

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

*Skin contact:*

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

*Eye contact:*

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

*Ingestion:*

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

*Burns:*

Rinse with water until pain stops then continue to rinse for 30 minutes.

### 4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of

other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

If eye irritation persists: Get medical advice/attention.

#### **Information to medics**

Bring this safety data sheet or the label from this product.

### **SECTION 5: FIREFIGHTING MEASURES**

#### **5.1. Extinguishing media**

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.  
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### **5.2. Special hazards arising from the substance or mixture**

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health.

Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

#### **5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: ●3Y

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

#### **6.2. Environmental precautions**

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

#### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local

regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof electrical/lighting/ventilating equipment.

Use non-sparking tools.

Take action to prevent static discharges.

The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.

Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap. Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:

1. Material appears to be degraded and or contaminated.
2. Material appears to be discolored.
3. Deterioration or distortion of storage container.
4. Thermal shock (sunlight).
5. Age of material exceeds recommended storage time.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

*Recommended storage material:* Always store in containers of the same material as the original container.

*Storage conditions:* No specific requirements.

*Incompatible materials:* Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Ethanol

Long term exposure limit (8 hours) (ppm): 1000

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 1920

Propan-2-ol

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 999

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 1250

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.

EH40/2005 Workplace exposure limits (Fourth Edition 2020).

### DNEL

Ethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	206 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	343 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	114 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	380 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	950 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	1900 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	87 mg/kg bw/day

Propan-2-ol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	500 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	178 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	1000 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day
Short term – Systemic effects - General population	Oral	51 mg/kg bw/day

### PNEC

Ethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		960 µg/L
Freshwater sediment		3.6 mg/kg

Intermittent release (freshwater)		2.75 mg/L
Marine water		790 µg/L
Marine water sediment		2.9 mg/kg
Predators		380-720 mg/kg
Sewage treatment plant		580 mg/L
Soil		630 µg/kg

#### Propan-2-ol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Intermittent release (freshwater)		140.9 mg/L
Marine water		140.9 mg/L
Marine water sediment		552 mg/kg
Predators		160 mg/kg
Sewage treatment plant		2.251 g/L
Soil		28 mg/kg

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

*General recommendations:*

Smoking, drinking and consumption of food is not allowed in the work area.

*Exposure scenarios:*

There are no exposure scenarios implemented for this product.

*Exposure limits:*

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

*Appropriate technical measures:*

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Apply standard precautions during use of the product. Avoid inhalation of vapours.

*Hygiene measures:*

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

*Measures to avoid environmental exposure:*

No specific requirements.

### Individual protection measures, such as personal protective equipment

*Generally:*

No specific requirements.

*Respiratory Equipment:*  
No specific requirements.

*Skin protection:*  
No specific requirements.

*Hand protection:*  
No specific requirements.

*Eye protection:*  
No specific requirements.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Colour:</i>	No data available.
<i>Odour / Odour threshold:</i>	No data available.
<i>pH:</i>	No data available.
<i>Density (g/cm<sup>3</sup>):</i>	No data available.
<i>Kinematic viscosity:</i>	No data available.
<i>Particle characteristics:</i>	Does not apply to liquids.

#### Phase changes

<i>Melting point/Freezing point (°C):</i>	No data available.
<i>Softening point/range (°C):</i>	Does not apply to liquids.
<i>Boiling point (°C):</i>	No data available.
<i>Vapour pressure:</i>	No data available.
<i>Relative vapour density:</i>	No data available.
<i>Decomposition temperature (°C):</i>	No data available.

#### Data on fire and explosion hazards

<i>Flash point (°C):</i>	No data available.
<i>Flammability (°C):</i>	The material is ignitable.
<i>Auto-ignition temperature (°C):</i>	No data available.
<i>Lower and upper explosion limit (% v/v):</i>	No data available.

#### Solubility

<i>Solubility in water:</i>	No data available.
<i>n-octanol/water coefficient (LogKow):</i>	No data available.
<i>Solubility in fat (g/L):</i>	No data available.

### 9.2. Other information

<i>Oxidizing properties:</i>	No data available.
------------------------------	--------------------

*Other physical and chemical parameters:*

No data available.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation

Causes serious eye irritation.

#### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### **Symptoms related to the physical, chemical and toxicological characteristics**

**Irritation effects:** This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

**Neurotoxic effects:** This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

## **11.2. Information on other hazards**

### **Endocrine disrupting properties**

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

### **Other information**

Propan-2-ol has been classified by IARC as a group 3 carcinogen.

---

## **SECTION 12: ECOLOGICAL INFORMATION**

---

### **12.1. Toxicity**

Based on available data, the classification criteria are not met.

### **12.2. Persistence and degradability**

Based on available data, the classification criteria are not met.

### **12.3. Bioaccumulative potential**

Based on available data, the classification criteria are not met.

### **12.4. Mobility in soil**

No data available.

### **12.5. Results of PBT and vPvB assessment**

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

### **12.6. Endocrine disrupting properties**

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

### **12.7. Other adverse effects**

None known.

---

## **SECTION 13: DISPOSAL CONSIDERATIONS**

---

### **Waste treatment methods**

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

**EWC code**

Not applicable.

**Specific labelling**

**Contaminated packing**

Packaging containing residues of the product must be disposed of similarly to the product.

**SECTION 14: TRANSPORT INFORMATION**

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR/ADN/RID	UN1263	PAINT	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L Tunnel restriction code: (E) See below for additional information.
IMDG	UN1263	PAINT	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1263	PAINT	Transport hazard class: 3 Label: 3 Classification code: F1 	III	No	See below for additional information.

\* Packing group

\*\* Environmental hazards

**Additional information**

This product is within scope of the regulations of transport of dangerous goods.

ADR/ADN/RID / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

Hazchem Code: ●3Y

**14.6. Special precautions for user**

Not applicable.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

### SECTION 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

*Restrictions for application:*

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

*Demands for specific education:*

No specific requirements.

*Control of Major Accident Hazards (COMAH) - Categories / dangerous substances:*

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

*UK-REACH, Annex XVII:*

Ethanol is subject to UK-REACH restrictions (entry 40).  
Propan-2-ol is subject to UK-REACH restrictions (entry 40).

*Additional information:*

Tactile warning.

*Sources:*

The Health and Safety at Work etc. Act 1974 Regulations 2013.  
Control of Major Accident Hazards (COMAH) Regulations 2015.  
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.  
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.  
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

#### 15.2. Chemical safety assessment

No

### SECTION 16: OTHER INFORMATION

#### Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS = Chemical Abstracts Service  
CE = Conformité Européenne (European conformity)  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
CSA = Chemical Safety Assessment  
CSR = Chemical Safety Report  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EC = Effective concentration  
ED = Effective dose  
EINECS = European Inventory of Existing Commercial chemical Substances  
EL = Effective Loading  
ErC = Concentration associated with x% growth rate response  
ES = Exposure Scenario  
EUH statement = CLP-specific Hazard statement  
EuPCS = European Product Categorisation System  
EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
GWP = Global warming potential  
HP = Hazardous Property code  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IC = X maximum inhibitory concentration  
IMDG = International Maritime Dangerous Goods  
LC = Lethal concentration  
LCLo = Value is the lowest concentration of a material in air reported to have caused the death of animals or humans  
LD = Lethal dose  
LOAEC = Lowest Observed Adverse Effect Concentration  
LOAEL = Lowest Observed Adverse Effect Level  
LOEC = Lowest Observed Effect Concentration  
LogKow = logarithm of the n-octanol/water coefficient  
LL = Lethal Loading  
M = For multiplication factor  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
NOAEC = No Observed Adverse Effect Concentration  
NOAEL = No Observed Adverse Effect Level  
NOEC = No Observed Effect Concentration  
NOELR = No Observable Effect Loading Rate  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

### **Additional information**

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

### **The safety data sheet is validated by**

Emma Christensen

### **Other**

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en