Industrial Oil 1505 Hardwax

Industrial oxidizing oil for wooden floors and furniture that combines oil and wax



Industrial Hardwax Oil 1505 is a high-performance and fast air-drying wood finish based on natural vegetable oils with high penetration. The hardwax oil is extremely suitable for production of beautiful, durable and smooth “factory-finished” floor solutions offering strong and long-lasting protection combined with an effective and flexible application process on the roller coater.

- Easy and flexible handling in production
- Extreme protection of the wood
- Factory-finished floors and furniture, ready for installation
- No additional on-site surface treatment is required
- Available in customized colours

Toepassingsgebied

For surface treatment of wooden floors, worktops and furniture.

Gebruik

Voorbereiding
The wood must be clean, dry and free from dust.

Schuurkorrels
Korrel 100-120.

Korrel voor tussenschuren
Korrel 320-400.

Opmerking
Viscosity correction: Correction can be made with WOCA Solvent only, #328575I.

Verwerkingswijze

The product must be stirred before and during application. Application method: Roller coater, Nitrile or natural rubber, shore 20-30. Number of coats: The oil may be applied on one or two roller stations. Application amount: Depends on the type of wood: Hardwood: approx. 25-30 gr/m². Softwood: approx. 40 gr/m². The surface needs to be polished before drying. Second coat: Approx. 10 gr/m² after 8 hours of drying. Note: Quantities are only recommendations and may vary.

Droogtijden

Volledig uitgehard : 7 dagen bij 20°C

Technische gegevens

VOS: 460 g/l, maximale grenswaarde (A/i (OB)): 500 g/l.

Dichtheid: 0.95-1.00 g/ml.

Houdbaarheid: 3 jaar

Rendement: 30-40 m²/L

Kleuren: Naturel

Bewaren: +10-25°C. Buiten het bereik van kinderen houden. Niet blootstellen aan hittebronnen (bijv. zonlicht). Bewaar vorstvrij tijdens de winter en koel in de zomer.

Verpakkingsgroottes: 20 L

Viscositeit: 70-75 Twe. DIN Cup 4

Drogestofgehalte: 50-55%

Onderhoud en bijbehorende producten

Reiniging en onderhoud
The industrial surface treatment can be maintained with WOCA maintenance products.

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

De vermelde informatie is gebaseerd op uitgebreide laboratoriumtesten en in de praktijk opgedane ervaringen. Aangezien WOCA veelal geen invloed heeft op de omstandigheden waarin het product wordt gebruikt, kunnen we enkel de kwaliteit van het product in kwestie garanderen. WOCA Denmark A/S is niet aansprakelijk voor een onjuist gebruik en/of verwerking van het product. Aangezien de resultaten afhangen van de constructie, de aard van het oppervlak, de voorbehandeling, temperatuur, luchtvochtigheid, gebruik etc., kan onderhavig product in principe worden aangemerkt als een tussenproduct. WOCA Denmark A/S behoudt zich het recht voor om het product evenals de verstrekte informatie zonder voorafgaande kennisgeving te wijzigen. Onderhavig label/ productbeschrijving vervangt alle voorgaande versies.