

Industrial Lye



Minimizes yellowing of wood

Industrial Lye bleaches down lighter hardwood and minimizes the natural occurrence of the wood turning yellow. It may also be used on exotic types of wood.

- Minimizes yellowing
- Can be used on all types of wood
- Instant lightening of wood
- Must be treated afterwards with WOCA oils or WOCA lacquers
- Minimizes colour variation of the wood

Toepassingsgebied

For all types of untreated wood.

Gebruik

Vorbereiding

The wood must be clean, dry and free from dust.

Schuurkorrels

Korrel 100-120.

Korrel voor tussenschuren

Korrel 400-500.

Verwerkingswijze

The product must be stirred before and during application.

Application method:

Sponge roller coater: 20-35 gr/m².

Spraying chamber: 20-50 gr/m². Manually: 20-50 gr/m².

Number of coats: Usually one coat.

Note: Product cannot stand alone! Must be treated with WOCA oils afterwards.

Verwerking	Spuitmond grootte (mm)	Spraydruk (bar)
handmatig	-	-
Airmix	13-17	40-60
Cup	1.0-1.5	3-4

Technische gegevens

VOS: 10 g/l, maximale grenswaarde (A/g (VB)): 30 g/l.

Dichtheid: 1.00-1.10 g/ml.

PH-waarde: pH 9-10

Houdbaarheid: 3 jaar

Verbruik: 40-50 m²/L

Kleuren: White, Natural

Verpakking: 25 L - 30 L - 1000 L

Viscositeit: 10-15 Tve. DIN Cup 4

Onderhoud en bijbehorende producten

Reiniging en onderhoud

The industrial surface treatment can be maintained with WOCA maintenance products.

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

De vermelde informatie is gebaseerd op uitgebreide laboratoriumtesten en in de praktijk opgedane ervaringen. Aangezien WOCA veelal geen invloed heeft op de omstandigheden waarin het product wordt gebruikt, kunnen we enkel de kwaliteit van het product in kwestie garanderen. WOCA Denmark A/S is niet aansprakelijk voor een onjuist gebruik en/of verwerking van het product. Aangezien de resultaten afhangen van de constructie, de aard van het oppervlak, de voorbehandeling, temperatuur, luchtvochtigheid, gebruik etc., kan onderhavig product in principe worden aangemerkt als een tussenproduct. WOCA Denmark A/S behoudt zich het recht voor om het product evenals de verstrekte informatie zonder voorafgaande kennisgeving te wijzigen. Onderhavig label/ productbeschrijving vervangt alle voorgaande versies.