

Furniture Primer



Priming of wood furniture before lacquering

Furniture Primer is a water-based single-component product designed to make the lacquer stick more easily to the wood and prevent colours from bleeding through. It is environmentally friendly and perfect for maintaining the wood's natural look and beautiful grain structure. Furniture Primer is easy to sand and can be applied to many types of wood, e.g. oak, merbau, iroko, teak and mahogany.

- Increases adhesion of lacquer
- Blocks stains
- Maintains the natural look of the wood
- Ideal for tropical wood species
- Non-toxic product

Toepassingsgebied

For priming of furniture made of hardwood, softwood, solid wood and veneer.

Gebruik

Vorbereiding

The wood must be clean, dry and free from dust.

Schuurkorrels

Korrel 240-320.

Korrel voor tussenschuren

Korrel 400-500.

Opmerking

The quality and uniformity of the wood and the intermediate sanding are crucial to the final surface finish. Remove residue after sanding as prescribed.

Verwerkingswijze

The product must be stirred before and during application.

Number of coats:

One coat.

Application amount:

- Apply the primer: 70-100 g/m².

- Leave to dry for 2 hours, depending on the air humidity and temperature.

- Sand intermediate with sanding grit 400-500 before applying the sealer or the lacquer.

Note:

We do not recommend intermediate sanding when using the white primer.

Verwerking	Spuitmond grootte (mm)	Spraydruk (bar)
handmatig	-	-
Airmix	13-17	40-60
Cup	1.5	3-4

Technische gegevens

VOS: 125 g/l, maximale grenswaarde (A/e (VB)): 130 g/l.

Dichtheid: 1.00-1.10 g/ml.

Houdbaarheid: 2 jaar

Verwerkingstemperatuur: +15-25°C en ca. 50% luchtvochtigheid.

Rendement: 10-15 m²/L

Bewaren: +10-25°C. Buiten het bereik van kinderen houden. Niet blootstellen aan hittebronnen (bijv. zonlicht). Bewaar vorstvrij tijdens de winter en koel in de zomer.

Drogestofgehalte: 20-30%

Onderhoud en bijbehorende producten

Reiniging en onderhoud

The industrial surface treatment can be maintained with WOCA maintenance products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

De vermelde informatie is gebaseerd op uitgebreide laboratoriumtesten en in de praktijk opgedane ervaringen. Aangezien WOCA veelal geen invloed heeft op de omstandigheden waarin het product wordt gebruikt, kunnen we enkel de kwaliteit van het product in kwestie garanderen. WOCA Denmark A/S is niet aansprakelijk voor een onjuist gebruik en/of verwerking van het product. Aangezien de resultaten afhangen van de constructie, de aard van het oppervlak, de voorbehandeling, temperatuur, luchtvochtigheid, gebruik etc., kan onderhavig product in principe worden aangemerkt als een tussenproduct. WOCA Denmark A/S behoudt zich het recht voor om het product evenals de verstrekte informatie zonder voorafgaande kennisgeving te wijzigen. Onderhavig label/ productbeschrijving vervangt alle voorgaande versies.