Neutral Oil 840004

Fast-drying industrial oxidizing oil for wooden floors

Neutral Oil Industry is an environmentally friendly product based on vegetable oils, water and drying agents. It is used for new or newly sanded wood and creates a neutral finish that resembles untreated wood. The oil offers a good protection of the surface while maintaining the raw wood look.

- Untreated appearance of the wood (invisible look)
- Roller application
- Easy application on a variety of processes
- Fast drying

Toepassingsgebied

For surface treatment of wooden floors and parquets in solid wood, hardwood and softwood.

Gebruik

Voorbereiding
The wood must be clean, dry and free from dust.

Schuurkorrels
Korrel 100-120.

Korrel voor tussenschuren
Korrel 320-400.

Opmerking
Viscosity correction: Correction can be made with a maximum of 5 % water. An extra coat of Industrial Hardwax oil 1505 can be applied giving extra protection.

Verwerkingswijze

The product must be stirred before and during application.

Application method:
Roller coater, Nitrile or natural rubber, shore 20-30 or sponge roller.

Number of coats:
The oil may be applied on one or two roller stations.

Application amount:
Depends on the type of wood:
Hardwood: approx. 20-30 gr/m2. Softwood: approx. 40 gr/m2.
Second coat: approx. 10 gr/m2 after 4 hours of drying.

Note:
Quantities are only recommendations and may vary. For improved chemical resistance it is recommended to apply WOCA Industrial Oil 1505 as a final topcoat.

Droogtijden

Volledig uitgehard : 7 dagen bij 20°C

Technische gegevens

VOS: 110 g/l, maximale grenswaarde (A/i (VB)): 140 g/l.

Dichtheid: 1.00-1.10 g/ml.

Houdbaarheid: 2 jaar

Rendement: 25-40 m²/L

Kleuren: Naturel

Bewaren: +10-25°C. Buiten het bereik van kinderen houden. Niet blootstellen aan hittebronnen (bijv. zonlicht). Bewaar vorstvrij tijdens de winter en koel in de zomer.

Verpakkingsgroottes: 20 L

Viscositeit: 80-85 Twe. DIN Cup 4

Onderhoud en bijbehorende producten

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

Reiniging en onderhoud
The industrial surface treatment can be maintained with WOCA maintenance products

De vermelde informatie is gebaseerd op uitgebreide laboratoriumtesten en in de praktijk opgedane ervaringen. Aangezien WOCA veelal geen invloed heeft op de omstandigheden waarin het product wordt gebruikt, kunnen we enkel de kwaliteit van het product in kwestie garanderen. WOCA Denmark A/S is niet aansprakelijk voor een onjuist gebruik en/of verwerking van het product. Aangezien de resultaten afhangen van de constructie, de aard van het oppervlak, de voorbehandeling, temperatuur, luchtvochtigheid, gebruik etc., kan onderhavig product in principe worden aangemerkt als een tussenproduct. WOCA Denmark A/S behoudt zich het recht voor om het product evenals de verstrekte informatie zonder voorafgaande kennisgeving te wijzigen. Onderhavig label/ productbeschrijving vervangt alle voorgaande versies.