

# Clean and Care Kit for Oiled Wood



## Revitalises oil-treated wood

All you need for maintenance and cleaning of oiled floors in one box. The Maintenance Oil may be used for the maintenance of all oxidative oiled wood surfaces and is especially suitable for the regular maintenance of oiled wood floors. Maintenance Oil refreshes the natural, warm glow of the wood and is suitable for both manual and machine application to oiled floors. The Natural Soap is used for regular cleaning and is a mild, penetrating soap that removes dirt and helps prevent the wood from drying out and cracking.

- All you need – in one box
- Makes oiled floors even more durable
- Highlights the glow and the grain structure of the wood
- Indoor climate certified
- Easy to apply

## Application area

For cleaning and care of all oxidative oiled wood surfaces, especially floors. The Maintenance Oil can be applied manually with a polishing pad and by machine (floors larger than 8-10 m<sup>2</sup>).

## Work description

### Preparation

When applying the oil please ensure that product, room and floor temperature should be between 15–35°C. Ensure good ventilation at all times during the application and drying time. Clean the floor with WOCA Intensive Wood Cleaner. Leave the floor to dry for at least 8 hours. The floor must be completely dry.

### Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

### Please note

Do not clean the floor or expose it to water during the first 3 days, while the oil is curing. Natural Soap is used for regular cleaning after the floor has been maintained with Maintenance Oil. Please follow the work instructions on the different products.

## Drying time

**Drying time when machine polished :** 3-4 hours at 20°C

**Drying time when hand polished :** 24-48 hours at 20°C

**Fully hard :** 3 days at 20°C

## Technical data

**Density:** 0.85-0.90 g/ml.

**Shelf life:** 3 years

**Application Temperature:** +15-30°C and approx. 50% air humidity.

**Coverage:** 30-40 m<sup>2</sup>/L

**Colours:** Natural

**Cleaning of tools:** Use WOCA Solvent or turpentine

**Storage:** +10-30°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

**Packaging:** 1 L

**Viscosity:** 15-20 Sec. DIN Cup 4

**Dilution:** WOCA Solvent (does not normally need to be diluted).

**Odour:** Characteristic

**Solid content:** 40-50%

## Maintenance and related products

WOCA Denmark A/S  
Tvæervej 6  
DK - 6640 Lunderskov  
+45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

### Maintaining and cleaning

For daily cleaning, WOCA Natural Soap is recommended, which effectively washes and cares for the wood. Supplement occasionally with WOCA Oil Refreshing Soap, which also adds a little oil to the wood with each wash.

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*