

# Neutral Oil 840004



## Fast-drying industrial oxidizing oil for wooden floors

Neutral Oil Industry is an environmentally friendly product based on vegetable oils, water and drying agents. It is used for new or newly sanded wood and creates a neutral finish that resembles untreated wood. The oil offers a good protection of the surface while maintaining the raw wood look.

- Untreated appearance of the wood (invisible look)
- Roller application
- Easy application on a variety of processes
- Fast drying

### Application area

For surface treatment of wooden floors and parquets in solid wood, hardwood and softwood.

### Work description

#### Preparation

The wood must be clean, dry and free from dust.

#### Sanding grits

Grit 100-120.

#### Intermediate sanding grits

Grit 320-400.

#### Please note

Viscosity correction: Correction can be made with a maximum of 5 % water. An extra coat of Industrial Hardwax oil 1505 can be applied giving extra protection.

### How to apply

The product must be stirred before and during application.

#### Application method:

Roller coater, Nitrile or natural rubber, shore 20-30 or sponge roller.

#### Number of coats:

The oil may be applied on one or two roller stations.

#### Application amount:

Depends on the type of wood:

Hardwood: approx. 20-30 gr/m<sup>2</sup>. Softwood: approx. 40 gr/m<sup>2</sup>.

Second coat: approx. 10 gr/m<sup>2</sup> after 4 hours of drying.

#### Note:

Quantities are only recommendations and may vary. For improved chemical resistance it is recommended to apply WOCA Industrial Oil 1505 as a final topcoat.

### Drying time

**Fully hard** : 7 days at 20°C

### Technical data

**VOC:** 110 g/l, maximum VOC content (A/i (WB)): 140 g/l.

**Density:** 1.00-1.10 g/ml.

**Shelf life:** 2 years

**Coverage:** 25-40 m<sup>2</sup>/L

**Colours:** Natural

**Storage:** +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

**Packaging sizes:** 20 L

**Viscosity:** 80-85 Sec. DIN Cup 4

## Maintenance and related products

WOCA Denmark A/S  
Tværvej 6  
DK - 6640 Lunderskov  
+45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

### Maintaining and cleaning

The industrial surface treatment can be maintained with WOCA maintenance products

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*