



# UV Topcoat

## Gives exceptional durability and gives very good abrasive resistance

UV Topcoat is a 100% UV product with no VOC. Available in various gloss levels, 5-20. The product offers exceptional durability and excellent resistance to abrasion.

- Exceptional durability
- No VOC
- Smooth surface
- Ultra matt finish

### Application area

For surface treatment of wooden floors in hardwood and softwood

### Work description

#### Preparation

Surface need to be clean, dry and free from dust.

#### Please note

It is mandatory to complete with full UV Lacquer system. UV Topcoat can not stand alone.

#### Number of coats

1-2

### How to apply

UV Sanding Sealer should be applied with 2 coats with 5-8 gr/m<sup>2</sup>. UV full semi cure 65-135 mJ/cm<sup>2</sup> after first coat and full cure 180 mJ/cm<sup>2</sup> after second coat.

Cleaning of roller and pump use WOCA UV Cleaner № 800525

### Drying time

**Drying time** : UV full cure 180 mJ/cm<sup>2</sup>

**Fully hard** : Immediately after UV-drying

### Technical data

**VOC**: 0 g/l, maximum VOC content (A/e (SB)): 400 g/l.

**Density**: 1.20-1.30 g/ml.

**Shelf life**: 2 years

**Coverage**: 5-10 g/m<sup>2</sup>

**Colours**: Natural

**Storage**: +10-35°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

**Packaging sizes**: 20 L

**Viscosity**: 45-55 Sec. DIN Cup 6

**Solid content**: 100% UV

**Mixing ratio**: Ready to use. Do not dilute.

### Maintenance and related products

WOCA Denmark A/S  
Tværvej 6  
DK - 6640 Lunderskov  
+45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*