

Furniture Glaze



Will add depth and character to each piece

Furniture Glaze are water-based colours used to create decorative effects

- Create fantastic colours
- Water-based
- Fast drying

Application area

For colouring of furniture made of hardwood, softwood, solid wood and veneer. Furniture Glaze will not be used on untreated wood

Work description

Preparation

The furniture must be clean, dry and free from dust.

Please note

To achieve the right quality/design it's important to apply Furniture Glaze on an already treated piece of furniture. Can't be applied on untreated wood

Number of coats

1

How to apply

The product must be stirred before and during application.

Number of coats:

One coat.

Application amount:

- Apply: 20-50 g/m². Leave to dry for 1-2 hours, depending on the air humidity and temperature.

- After 2 hours of drying, the surface is ready for treatment with WOCA Furniture Lacquer.

Note:

The product can be diluted with up to 20% water before application.

Application	Nozzle size (mm)	Spray pressure (bar)
Manual	-	-
Airmix	-	40-60
Cup	1.5	-

Technical data

VOC: 230 g/l, maximum VOC content (A/e (WB)): 130 g/l.

Density: 1.00-1.10 g/ml.

pH-value: pH 8-9

Shelf life: 2 years

Coverage: 20-40 m²/L

Colours: Colourless

Cleaning of tools: Use warm water

Storage: +10-35°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 10 L

Dilution: Ready mixed. if necessary, it is possible to dilute with water max. 20%.

Specific gravity: 1.00-1.10 g/ml.

Solid content: 20-30%

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.