UV Primer WB



Give extra adhesion to the wood

UV Primer WB is a water-based product which give excellent adhesion to all types of wood including tropical wood species. It can be tinted with WOCA water-based pigments in various colours from untreated look to very colourful.

- Give excellent adhesion
- Water-based
- No UV-curing needed
- Can be tinted with WOCA Pigments water-based

Application area

All types of hardwood, softwood, solid wood and veneer.

Work description

Preparation
Wood need to be sanded well with grit 120-180 and must be clean, dry and free from dust.

Sanding grits
Grit 120-180.

Please note
UV Primer WB require no UV drying before next coat. Viscosity correction: Correction can be made with 5% demineralized water. It's mandatory to complete with full UV Lacquer system. UV Primer WB can't stand alone

Number of coats
1

How to apply

UV Primer WB should be applied by 1 coat 8-15 g/m².
Roller and pumps should be cleaned with WOCA Cleaner for water-based products # 800425

Drying time

Drying time : No UV light is needed before applying next product

Technical data

VOC: 0 g/l, maximum VOC content (A/e (SB)): 400 g/l.

Density: 1.10-1.20 g/ml.

Shelf life: 2 years

Coverage: 8-15 g/m²

Colours: Natural

Storage: +10-35°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 20 L

Viscosity: 30-40 Sec. DIN Cup 6

Specific gravity: 1.10-1.20 g/ml.

Solid content: 60-65%

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.