

# OUTDOOR WOOD OIL



## Outdoor wood oil

Woodcare+ Outdoor Wood Oil is a solvent-based oil for all exterior woodwork. Its thin consistency ensures deep penetration into the wood fibers, saturating the wood and effectively keeping moisture out. The oil is ideal for worn, dried-out, and previously treated wood, reviving its resilience and leaving a beautiful finish that highlights the natural grain.

- Penetrates wood fibers deeply and quickly
- Protects the wood against moisture
- Enhances the natural wood structure
- For all exterior woodwork

## Application area

The oil can be used for a wide range of outdoor woodwork, including terraces, garden furniture, windows, and more.

## Work description

### Preparation

Clean the wood with Woodcare+ Outdoor Wood Cleaner before treatment. Allow it to dry for at least 24 hours (max. 15% moisture content). Apply the oil in dry weather at min. 13°C. Avoid direct sunlight and high heat during application.

### Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

## Drying time

**Drying time :** 4-5 hours at 20°C

**Between coats :** 4-6 hours at 20°C

**Fully hard :** 24-48 hours at 20°C

## Technical data

**VOC:** 0 g/l, maximum VOC content (A/f (SB)): 700 g/l.

**Density:** 1.00-1.10 g/ml.

**Shelf life:** 2 years

**Coverage:** 8-10 m<sup>2</sup>/L

**Colours:** Larch, Nyatoh, Teak, Walnut

**Cleaning of tools:** Use turpentine

**Storage:** +5-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

**Packaging sizes:** 2.5 L

**Dilution:** Turpentine

**Moisture content:** The moisture content of the wood must not exceed 15%

**Odour:** Strong

## Maintenance and related products

WOCA Denmark A/S  
Tværvej 6  
DK - 6640 Lunderskov  
+45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*