



WOOD FLOOR OIL

Oiling of Wooden Floors

Woodcare+ Wood Floor Oil penetrates deep into the wood, creating a durable surface with high resistance to water and dirt. Ideal for indoor use on all untreated, new, or freshly sanded surfaces.

- Penetrates deeply and effectively protects the wood
- Guards against water and dirt
- Suitable for all untreated, new, or freshly sanded indoor wood surfaces.

Application area

For untreated, new or newly-sanded wooden surfaces.

Work description

Preparation

The surface must be clean and completely dry before applying the oil. For freshly sanded surfaces, it is important to vacuum thoroughly.

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Please note

Avoid exposing the surface to water or cleaning during the first 7 days while the oil cures. After this period, the floor can be cleaned with Woodcare + Floor Soap, which provides extra protection.

Drying time

Drying time : 12-24 hours at 20°C

Fully hard : 7 days at 20°C

Technical data

VOC: 0 g/l, maximum VOC content (A/i (SB)): 500 g/l.

Density: 0.90-0.95 g/ml.

Shelf life: 3 years

Application Temperature: +15-25°C and approx. 50% air humidity.

Coverage: 10-12 m²/L

Colours: Natural, White, Extra White

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging: 2.5 L

Dilution: WOCA Solvent (does not normally need to be diluted).

Solid content: 50-55%

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.