

Hardfloor Cleaner



Cleaning of vinyl, linoleum, and LVT floors

Hardfloor Cleaner ensures quick and effective cleaning of vinyl, linoleum, and LVT floors. The product easily removes dirt and grime, leaving a strong and resilient surface. Since the product does not build up a soap film, it is ideal for areas that require frequent cleaning. It can also be used on painted floors, tiles, and other non-absorbent surfaces.

- Suitable for vinyl, linoleum, and LVT floors
- Quick and efficient cleaning
- Easily removes dirt and grime
- Leaves a strong and resilient surface
- Ideal for frequent cleaning

Application area

For vinyl, linoleum, and LVT floors

Work description

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

The floor is thoroughly cleaned with Hardfloor Cleaner in the mixing ratio of 125 ml to 5 liters of water.

Drying time

Drying time : 15-30 minutes at 20°

Technical data

Declaration: < 5%: Nonionic surfactants. Preservative (BENZISOTHIAZOLINONE)

VOC: g/l, maximum VOC content (A/i (WB)): 140 g/l.

Density: 1.00-1.10 g/ml.

pH-value: pH 8-9

Shelf life: 3 years

Application Temperature: +15-30°C and approx. 50% air humidity.

Coverage: 320-400 m²/L

Colours: Colourless

Cleaning of tools: Use warm water

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 2.5 L

Dilution: Water

Odour: Odourless

Mixing ratio: 125 ml to 5 L water.

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.