



Hardfloor Intensive Cleaner

Cleaning and wet grinding of hard floors

WOCA Hardfloor Intensive Cleaner is developed for effective cleaning and preparation of all types of elastic and hard floor coverings, such as linoleum, vinyl, and PVC. The product can be used for both wet sanding and thorough cleaning of floors, as well as for the removal of stubborn stains. Ideal as a pre-treatment before applying PU Coating, where it ensures a clean and optimally prepared surface.

- Suitable for both wet grinding and basic cleaning
- For all elastic and hard floor types (linoleum, vinyl, PVC)
- Ensures optimal adhesion of Woca Hardfloor PU-Coating
- Ensures a clean and uniform surface before treatment
- Effective removal of grease, dirt, and stubborn stains

Application area

Work description

Preparation

Mixing ratios: For wet grinding: 100ml to 1L water (1:10) General cleaning: 100ml to 4L water (1:40)

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Please note

Woca Hardfloor Intensive Cleaner must NOT be used for regular daily cleaning.

Drying time

Drying time : 2-8 hours at 20°C

Technical data

Declaration: >5% ≤15%: Nonionic surfactants

Density: 1.00-1.10 g/ml.

pH-value: pH 10-11

Shelf life: 3 years

Application Temperature: +15-30°C and approx. 50% air humidity.

Coverage: 200-300 m²/L

Colours: Colourless

Cleaning of tools: Use warm water

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 2.5 L

Dilution: Water

Odour: Faint

Mixing ratio: 100 ml for 1.0 L water

Maintenance and related products

Maintaining and cleaning

For daily cleaning of elastic and hard floor coverings, such as linoleum, vinyl, and PVC, Woca Hardfloor Cleaner is recommended.

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.